


D-SUB CONNECTOR CONTACTS



🛃 3D PDF

TE CONNECTIVITY (TE) 20 DF PIN CONT L.P. AMPLIMITE | Crimp Snap

745254-6 TE Internal Number: 745254-6 Alias ID: 1147577, AMP-0-0745254-6, D57505-000

Always EU RoHS/ELV Compliant

Contact Type Pin Contact Style Crimp Snap-in Contact Size 20

Contact Base Material **Brass**

Contact Mating Area Plating Material **Gold**

Product Drawings	PIN CONTACT, SIZE 20 DF, 22-26 AWG, W/.040050 DIA INSULATION SUPPORT PDF English	
CAD Files	Customer View Model 3D_IGS.ZIP English	
	Customer View Model 3D_STP.ZIP English	
	3D PDF PDF 3D	
	Customer View Model 2D_DXF.ZIP English	
Catalog Pages/Data Sheets	AMP Circular Connectors For Commercial Signal & Power Applications PDF English	
	AMPLIMITE Subminiature D Connectors - Cable Connectors PDF English	
	Signal Contacts PDF English	
Product Specifications		
Product Specification	AMPLIMITE HDP-20 Subminiature D Connector With F Crimp Contacts	
Application Specification	English AMPLIMITE HDP-20 And Economy Crimp Snap Subminiature D Commercial Connectors PDF English	

HD-20 Precision Formed Contacts

У 🖬 f 🔻

TE Material Declaration	MD 745254 (0007201252 distant
TE Material Declaration	MD_745254-6_0807201352_dmtec PDF
	English
Instruction Sheets	
Instruction Sheet (U.S.)	AMPLIMITE High Density (HDP-20) Connectors With Crimp-Type Contacts
	PDF English
	Insertion/Extraction Tool 91285-1 And Replacement Tip Kits 543382-[]
	PDF English
	PRO-CRIMPER III Hand Crimping Tool Assembly 58448-2 With Die Assembly
	58448-3
	PDF English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Grade	Standard	
	Insulation Support	Yes	
	Product Type	Contact	
Body Features	Color Code	Yellow Dot	
Contact Features	Contact Type	Pin	
	Contact Style	Crimp Snap-in	
	Contact Size	20	
	Contact Base Material	Brass	
	Contact Mating Area Plating Material	Gold	
	Pin Diameter	1.02 mm [.04 in]	
	Contact Mating Area Plating Thickness (µin)	30	
Termination Features	Termination Method to Wire/Cable	Crimp	
Mechanical Attachment	Contact Retention in Housing	Crimp Snap-In	
Dimensions	Wire Range	.15 – .4 mm² [26 – 22 AWG]	
	Wire Insulation Diameter	1.01 – 1.27 mm [.04 – .05 in]	
	Insulation Diameter (Max) (in)	.05	

Operation/Application	For Use With	AMPLIMITE HDP-20, CPC Connectors
Packaging Features	Packaging Method Packaging Quantity	Loose Piece 1000
Product Compliance	Statement of Compliance PDF	

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

D-SUB CONNECTOR CONTACTS	WIRE-TO-BOARD HEADERS & RECEPTACLES	RECTANGULAR POWER CONNECTORS	CRIMP D-SUB CONNECTORS
and the second second			
20 DF SOCKET CONT L.P. 745253-6	03P MTA100 CONN ASSY RED LF 3-641190-3	SOCKET BLOCK .200 GRID 203622-2	KIT, HDP-20, ENCLSUR, PLUG, SIZE 3 1658659-1
Save to List	Save to List	Save to ListFind Similar Products	 Save to List Find Similar Products

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Contacts category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below :

173112-0723173112-0393173112-0389173112-0750173112-0912FMP009P104FMP010P104FMP010S104FMP016P104FMP016S104FMP051S110FMX006S128B124C25029X131A11039X132A11019X132J22039X132A11029X132A12059X132C12029XRMPIR01S02E2RLFDM53744-11757912-1188582-000162A11839X162A11889X1757913-1FK20S18-02V_100FMP006S110FMP009S104FMP139S115212558-1D02-22-26P-10000L17DM53744217D-610-10CS2820030-1955-000030-50634053744-0098053744-0099053745-0115053745-0111601064N004601098N0036-745288-2D-610-10CS296286303057NLFDM537425001NCLF131A11019X173112-0045162A11819X1731120397