



# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING  
English

3D PDF

## TE CONNECTIVITY (TE) 12 MODII HDR DRST SHRD .100CL

AMPMODU | AMPMODU Headers

103169-4  
TE Internal Number: 103169-4

Not EU RoHS or ELV Compliant  
[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**  
Centerline **2.54 mm [ .1 in ]**  
Number of Positions **12**  
Header Type **Shrouded**

### Product Drawings

[HDR ASSY, MOD II, SHROUDED, 4 SIDES, DBL ROW, VERTICAL, .100X.100 C/L, WITH .025 SQ POSTS](#)

PDF  
English

### CAD Files

#### Customer View Model

2D\_DXF.ZIP  
English

#### 3D PDF

PDF  
3D

#### Customer View Model

3D\_IGS.ZIP  
English

#### Customer View Model

3D\_STP.ZIP  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Applies To	<b>Printed Circuit Board</b>
Connector Style	<b>Plug</b>
PCB Mounting Orientation	<b>Vertical</b>
Connector Type	<b>Header</b>
Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
Stabilizers	<b>Without</b>
Strain Relief	<b>Without</b>

	Strain Relief	<b>Without</b>
	Board Standoff	<b>Without</b>
	Profile	<b>Standard</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>
<hr/>		
Configuration Features	Number of Positions	<b>12</b>
	Number of Rows	<b>2</b>
	Keyed	<b>No</b>
	Selectively Loaded	<b>No</b>
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	<b>750 Vrms</b>
<hr/>		
Body Features	Header Type	<b>Shrouded</b>
	Post Size	<b>.64 mm [ .025 in ]</b>
<hr/>		
Contact Features	Contact Protection	<b>With</b>
	Contact Shape	<b>Square</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µin)	<b>30</b>
	Solder Tail Contact Plating Material	<b>Tin-Lead over Nickel</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Protection Type	<b>Shrouded</b>
Contact Current Rating (A)	<b>3</b>	
<hr/>		
Termination Features	Termination Post Length	<b>3.18 mm [ .125 in ]</b>
	Termination End Plating Thickness (µin)	<b>100 – 200</b>
	Termination End Plating Material	<b>Tin-Lead Over Nickel</b>
	Termination Method to PC Board	<b>Through Hole</b>
<hr/>		
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Retention	<b>Without</b>
	Mating Connector Lock Type	<b>Detent Windows</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment	<b>With</b>
	Mating Connector Lock	<b>With</b>

	Mating Alignment Type	Polarization
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>
	Housing Style	<b>4-Sided</b>
Dimensions	Shrouded End Dimension	<b>3.81 mm [ .15 in ]</b>
	PCB Thickness (Recommended)	<b>1.397 mm [ .055 in ]</b>
	Mating Post Length	<b>8.08 mm [ .318 in ]</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
	High Temperature Housing	<b>No</b>
Operation/Application	High Speed Serial Data Connector	<b>No</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
Packaging Features	Packaging Quantity	<b>208</b>
	Packaging Method	<b>Tray</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF  <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

Products - 1 Results

[View All](#)

Compare 0/10 

Relation Type 

RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - FFC Connectors  
FFC | FFC

**012 HOUSING FFC RCPT**  
DB 100CL 3 00170 4

Always EU RoHS/ELV Compliant

Connector Type **Housing**





DR 100CL - 3-001 / 7-4  
TE INTERNAL NUMBER: 3-88179-4

✓ Active

Connector Style **Receptacle**

Centerline **2.54 mm**

Number of Positions **12**

Number of Rows **2**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [67230-005LF](#)