

# **FFC CONNECTORS**





✓ Active



PRODUCT DRAWING



3D PDF

### TE CONNECTIVITY (TE)

# 006 HOUSING FFC PIN 100CL SR

FFC | FFC

485893-4

TE Internal Number: 485893-4

Always EU RoHS/ELV Compliant

Connector Type Housing

Connector Style Plug

Centerline 2.54 mm [.1 in]

Number of Positions 6

Number of Rows 1

**Product Drawings** 

HOUSING, PIN, W/DETENT SLOTS, . 100, FFC

PDF **English** 

CAD Files

3D PDF

PDF **English** 

Customer View Model

2D\_DXF.ZIP English

Customer View Model

3D\_IGS.ZIP English

Customer View Model

3D\_STP.ZIP **English** 

**Product Specifications** 

Product Specification Connector, Flexible Flat Conductor Cable, .100 Inch Centerline

PDF **English** 

Application Specification Flexible Flat Cable (FFC) Housings With Contact Cavities On 2.54-Mm (.100-In.]

**Centerline Spacing** 

PDF **English** 

Instruction Sheets

Instruction Sheet (U.S.) Extraction Tools 91047-[]

PDF **English** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.


Product Type Features	Connector Type	Housing
	Connector Style	Plug
	Applies To	Cable
	Type of Connector	Standard
	Wire/Cable Type	FFC
	Product Type	Connector
	Connector System	Wire-to-Board
Configuration Features	Number of Positions	6
	Number of Rows	1
Electrical Characteristics	Voltage	300 VAC
	Dielectric Withstanding Voltage (VAC)	720
	Insulation Resistance (M $\Omega$ )	5000
Body Features	Color	Black
Contact Features	Contact Type	Pin
Mechanical Attachment	Mating Connector Lock	With
	Mating Alignment	With
	Panel Mount Retention	Without
	Mating Alignment Type	Polarization
	Mating Connector Lock Type	Detent Windows
	Mating Retention	With
Housing Features	Centerline	2.54 mm [ .1 in ]
	Housing Color	Black
	Housing Material	Thermoplastic
Hanna Canditian-	Flore Potardort	Vac
Usage Conditions	Flame Retardant	Yes
Usage Conditions	Flame Retardant  Operating Temperature Range (°C)	Yes -65 – 105
Usage Conditions  Industry Standards		
	Operating Temperature Range (°C)	-65 – 105
	Operating Temperature Range (°C)	-65 – 105


**Product Compliance** 

Statement of Compliance

VIEW ALL PRODUCT COMPLIANCE

# **CUSTOMERS ALSO BOUGHT**







#### PRODUCT - CONTACTS

Connectors - FFC Contacts FFC | FFC

# FFC, PIN CONTACT, LP, ROUND WIRE,

- 1-86561-0

TE INTERNAL NUMBER: 1-86561-0

✓ Active

#### Always EU RoHS/ELV Compliant

Centerline 2.54 mm

Wire/Cable Type Round Wire,

Discrete

Contact Type **Pin** 

Contact Mating Area Plating

Material **Tin** 

Packaging Method Loose Piece

#### RELATIONSHIP

#### **Contacts**

Identifies Contacts compatible with a given Housing

See All Contacts



#### PRODUCT - CONTACTS

Connectors - FFC Contacts FFC | FFC

# FFC PIN CONTACT AU - 88048-4

TE INTERNAL NUMBER: 88048-4

✓ Active

#### Always EU RoHS/ELV Compliant

Centerline 2.54 mm

Wire/Cable Type Round Wire,

Discrete

Contact Type **Pin** 

Contact Mating Area Plating
Material **Gold Flash/Palladium** 

Nickel or Gold/Nickel

Packaging Method Reel



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for FFC & FPC Connectors category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

HFW11R-1STE1H1LF FH29B-100S-0.2SHW(99) FA5S008HP1 FH29B-120S-0.2SHW(99) FH29B-80S-0.2SHW(99) FHS-16 FPH-2022G
52610-1075 52610-1275 52610-1934 XF3M(1)-1415-1B-R100 501864-3091-TR225 0525594033 086210010340800 086222026001800
52271-2869-CUT-TAPE 62674-201121DLF 62684-36210E9ALF 52610-1675 52746-1671-TR250 10051922-2810EHLF 6-520415-9
BD021-09A-A1-0350-0200-0550-LD SFV6R-1STE9HLF XF3M-2915-1B-R100 1658549-1 62674-221121ALF 46214008010800
046298003000883 151660622 842-816-2630-035 AYF530665TA AYF351525 046296011930846+ AYF352325A 046254020000800+
FH19C-13S-0.5SH(99) FH39J-51S-0.3SHW(99) AYF355125A AYF530365TA FH29B-44S-0.2SHW(99) SFW5R-2STAE9LF AYF351125A
AYF350725A 62684-502100AHLF FH39-61S-0.3SHW(99) AYF414035A 10064555-172520HLF AYF212335A 504754-2500