



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)
4P RCPT VAL-U-LOK V2
[VAL-U-LOK](#) | [VAL-U-LOK](#)

794954-4
 TE Internal Number: 794954-4

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Board, Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **4**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[RECEPTACLE HOUSING, VAL-U-LOK\(TM\)](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

Product Specifications

Product Specification

[VAL-U-LOK Connectors](#)

PDF
English

Application Specification

[VAL-U-LOK Series Headers, Connectors And TPA Accessories](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_794954-4_06182014342_dmtec](#)

PDF
English

Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Receptacle
	Contact Type	Socket

Configuration Features	Number of Positions	4
	Centerline	4.2 mm [.165 in]
	Number of Signal Positions	4
	Number of Rows	2
	Row-to-Row Spacing	4.2 mm [.165 in]
	Multiple Contact Types	Without
	Contact Layout	Matrix, Square Grid

Electrical Characteristics	Operating Voltage (VAC)	600
----------------------------	-------------------------	------------

Termination Features	Wire/Cable Type	Discrete Wire
----------------------	-----------------	----------------------

Housing Features	UL Flammability Rating	UL 94V-2
	Housing Color	Natural
	Housing Material	Nylon

Dimensions	Length	9.6 mm [.378 in]
	Height	11.8 mm [.464 in]
	Accepts Wire Insulation Diameter Range	1.2 – 3.1 mm [.047 – .122 in]
	Width	20 mm [.787 in]


Usage Conditions	Sealed Condition	Not Sealed
	Insertion Force (Newton)	15

Operation/Application	Connector System	Wire-to-Board, Wire-to-Wire
	Applies To	Wire/Cable
	Operating Temperature	-40 – 105 °C [-40 – 221 °F]
	Circuit Application	Signal

Identification Marking	Circuit Identification Feature	With
------------------------	--------------------------------	-------------

Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	UL Rating	Recognized
	CSA File Number	208567
	Agency/Standard	CSA, UL
	VDE Tested	No
	Agency/Standard Number	E28476
Packaging Features	Packaging Method	Bag/Box
	Packaging Quantity	500
Other	For Use With	Printed Circuit Board
	Selectively Loaded	No
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

<p>POWER CONTACTS</p>  <p>VAL-U-LOK SKT PHBZ SN 24-18 LP 1586315-3</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p> <p>4P FH PLUG VAL-U-LOK V2 1586000-4</p> <p>Save to List Find Similar Products</p>	<p>POWER CONTACTS</p> <p>VAL-U-LOK PIN BR SN 16AWG 1586054-1</p> <p>Save to List Find Similar Products</p>	<p>CRIMP RINGS & SPADES</p> <p>TERMINAL, PIDG SPR SPD 16-14 5 52934-1</p> <p>Save to List Find Similar Products</p>
--	---	---	--

Products - 10 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS





Connectors - Rectangular Power Connectors
VAL-U-LOK | VAL-U-LOK

4P VAL-U-LOK R/A HDR V2 - 1586041-4

TE INTERNAL NUMBER: 1586041-4

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating **9 A**

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors
VAL-U-LOK | VAL-U-LOK

04 DUAC PLUG HSG 94V- 2 FR/HANG - 794542-4

TE INTERNAL NUMBER: 794542-4

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Board, Wire-to-Wire**

Applies To **Printed Circuit Board**

UL Flammability Rating **UL 94V-2**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors
VAL-U-LOK | VAL-U-LOK

4P VAL-U-LOK VRT HDR W/P V2 - 1586039-4

TE INTERNAL NUMBER: 1586039-4

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating **9 A**



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [67230-005LF](#)