



# CARD EDGE POWER CONNECTORS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## CONN SEC II 36 POS 100C/L

L, Standard

5530843-8

TE Internal Number: 5530843-8

Always EU RoHS/ELV Compliant

Circuit Application **Power, Signal**

Contact Current Rating (A) **3**

Number of Dual Positions **36**

Centerline **2.54 mm [ .1 in ]**

Termination Method to PC Board **Through Hole - Solder**

### Product Drawings

[CONNECTOR ASSEMBLY STANDARD EDGE II, .100 CENTERLINE](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

[POWER\\_CONNECTORS\\_CATALOG\\_SEC03\\_CARD\\_EDGE](#)

PDF  
English

### Product Specifications

Product Specification

[Connector, Standard Edge](#)

PDF  
English

Application Specification

[Standard Edge Card \(SEC\) II, SEC II Power, And High Current Card Edge Connectors](#)





PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Product Type	<b>Connector Assembly</b>
	Contact Type	<b>Socket</b>
Configuration Features	Number of Dual Positions	<b>36</b>
	Centerline	<b>2.54 mm [ .1 in ]</b>
	Position Keyed	<b>0</b>
	Row-to-Row Spacing	<b>4.85 mm [ .191 in ]</b>
	Number of Rows	<b>2</b>
	PCB Mounting Orientation	<b>Vertical</b>
Electrical Characteristics	Contact Current Rating (A)	<b>3</b>
	Operating Voltage	<b>400 V</b>
Contact Features	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Mating Area Plating Thickness (µm)	<b>.76</b>
	Contact Termination Area Plating Finish	<b>Matte</b>
	Contact Termination Area Plating Thickness (µin)	<b>100</b>
	Contact Termination Area Plating Thickness (µm)	<b>2.54</b>
	Contact Retention	<b>Without</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Underplate Material	<b>Nickel</b>
	Contact Termination Area Plating Material	<b>Tin</b>
Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
	Termination Post/Tail Length	<b>3.18 mm [ .125 in ]</b>
Mechanical Attachment	PCB Mount Retention	<b>With</b>
	Mating Retention	<b>Without</b>
	Mating Alignment	<b>With</b>
	PCB Mount Alignment	<b>Without</b>
	PCB Mount Retention Type	<b>Solder Tails</b>
	Mating Alignment Type	<b>Keyed</b>
Housing Features	Housing Color	<b>Black</b>
	End Caps	<b>Without</b>
	Housing Material	<b>Polyester GF</b>

Dimensions	Card Slot Depth	<b>7.49 mm [ .295 in ]</b>
	Height	<b>15.49 mm [ .61 in ]</b>
Operation/Application	Circuit Application	<b>Power, Signal</b>
	Connector System	<b>Board-to-Board</b>
	Applies To	<b>Printed Circuit Board</b>
	Operating Temperature Range (°C)	<b>-55 – 85</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Method	<b>Box</b>
	Packaging Quantity	<b>90</b>
Other	For Use With	<b>Printed Circuit Board</b>
	Selectively Loaded	<b>No</b>
	Positions Unloaded	<b>None</b>
Product Compliance	<a href="#">Statement of Compliance PDF</a> <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

<p>CARD EDGE POWER CONNECTORS</p>  <p>CONN SEC II 30 POS 100C/L 1-5530843-8</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>DIP &amp; SIP SWITCHES</p>  <p>DIP SW 4 POSN SEALED 3-435640-5</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>THROUGH-HOLE RESISTORS</p>  <p>LR1 1% 432R LR1F432R</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>CARD EDGE POWER CONNECTORS</p>  <p>CONN SEC II 30 POS 100C/L 5530843-7</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
--	--	---	--

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard Card Edge Connectors](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[6565204-6](#) [PKC-156](#) [1437274-4](#) [147889-1](#) [1489165-4](#) [EBT156-12B1X](#) [EBT15622B2X](#) [EBT156-22R2W](#) [1-582587-1](#) [1-582589-1](#) [2-6437275-9](#) [284-0102-12100](#) [306022901000000](#) [307-012-502-202](#) [307-024-526-201](#) [307-056-520-300](#) [307-080-526-208](#) [245-062-520-350](#) [287-0032-12101](#) [306-010-500-112](#) [306-028-525-102](#) [306-240-318](#) [307-036-502-202](#) [307-036-521-301](#) [307-072-526-202](#) [345-060-559-303](#) [368-004-520-201](#) [392-008-559-201](#) [534671-1](#) [5-530501-5](#) [341-240-317](#) [345-029-520-300](#) [345-030-500-301](#) [345-044-500-300](#) [345-220-058](#) [346-240-318](#) [357-030-526-201](#) [387-012-523-300](#) [395-044-520-300](#) [395-100-524-300](#) [50-12B-10](#) [50-6SN-5](#) [09-07-2032](#) [10035388-106LF](#) [10035388-802LF](#) [10122859-009LF](#) [10127905-B04B24BLF](#) [530555-1](#) [EBT156-15A2X](#) [2007209-1](#)