



KUP-14A55-24 Product Details

[Share](#) | [Print](#) | [Email](#)


KUP-14A55-24
(1393118-2)

TE Internal Number: 1393118-2

Active

View 3D PDF

Industrial Relays (General Purpose)

Converted to EU RoHS but not ELV Compliant (Statement of Compliance)

Product Highlights:

- KUP Series
- Contact - Current Class = 5A to 10A Class, Less Than 16A
- Contact - Rated Current = 10 A
- Terminal Type = Quick Connect, Solder
- Contact - Arrangement = 3 Form C (CO)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [KU KUP Enclosed Relay](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version D)
- [3D Model](#) (IGES, Version D)
- [3D Model](#) (STEP, Version D)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [PCB Layout](#)
- [Wiring Diagram](#)
- [Front View](#)

Related Products:

- [Tooling](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)

Mechanical Attachment:

- Mounting Options = Bracket Mount

Electrical Characteristics:

- Contact - Current Class = 5A to 10A Class, Less Than 16A
- [Contact - Rated Current \(A\)](#) = 10
- Contact - Limiting Continuous Current (A) = 10
- Contact - Limiting Making Current (A) = 10
- Contact - Limiting Breaking Current (A) = 10
- Insulation - Initial Dielectric Between Coil/Contact Class = 1500V to 2500VA Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 1200
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 2200
- Contact - Rated Voltage (VAC) = 240
- Contact - Limiting Short-Time Current (A) = 10
- Contact - Switching Recommended Load, Min. = 300mA at 12V
- Coil - Rated Voltage (VAC) = 24
- [Coil - Resistance \(Ω\)](#) = 72
- [Coil - Rated Power, AC \(VA\)](#) = 3.00
- Coil - Rated Power Class = 2.0VA to 3.0VA Class
- Insulation - Initial Dielectric Between Adjacent Contacts (V rms) = 2200
- Insulation - Initial Insulation Resistance (MΩ) = 100000

Dimensions:

- Mechanical - Length Class = 40mm to 50mm Class
- Length (mm [in]) = 48.40 [1.906]

Body Features:

- Mount Type = Panel Mount
- Weight (g [oz]) = 85.00 [2.988]

Contact Features:

- Terminal Type = Quick Connect, Solder
- Contact Material = AgCdO
- Contact - Number of Poles = 3

Configuration Features:

- [Contact - Arrangement](#) = 3 Form C (CO)
- [Coil - Magnetic System](#) = Monostable, AC
- Coil - Special Features = UL Coil Insulation Class B

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Approved/Registered Standards = UL, CSA

Environmental:

- Environmental - Category of Protection = RTI
- Environmental - Ambient Temperature, Max. (°C [°F]) = 45 [113]
- Environmental - Ambient Temperature Class = 0 to 50°C Class

Packaging Features:

- Packaging Method = Tray

- Mechanical - Width Class = 30mm to 40mm Class
- Width (mm [in]) = 38.90 [1.531]
- Mechanical - Height Class = 30mm to 40mm Class
- Height (mm [in]) = 35.70 [1.405]

Other:

- Series = KUP
- Brand = Potter & Brumfield

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [General Purpose Relays](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[APF30318](#) [JVN1AF-4.5V-F](#) [PCN-105D3MHZ](#) [5JO-10000S-SIL](#) [5JO-1000CD-SIL](#) [5JO-400CD-SIL](#) [LY2S-AC220/240](#) [LYQ20DC12](#)
[6031007G](#) [6131406HQ](#) [6-1393099-3](#) [6-1393099-8](#) [6-1393122-4](#) [6-1393123-2](#) [6-1393767-1](#) [6-1393843-7](#) [6-1415012-1](#) [6-1419102-2](#) [6-](#)
[1423698-4](#) [6-1608051-6](#) [6-1608067-0](#) [6-1616170-6](#) [6-1616248-2](#) [6-1616282-3](#) [6-1616348-2](#) [6-1616350-1](#) [6-1616350-8](#) [6-1616358-7](#) [6-](#)
[1616359-9](#) [6-1616360-9](#) [6-1616931-6](#) [6-1617039-1](#) [6-1617052-1](#) [6-1617090-2](#) [6-1617090-5](#) [6-1617347-5](#) [6-1617353-3](#) [6-1617801-8](#) [6-](#)
[1617802-2](#) [6-1618107-9](#) [6-1618248-4](#) [M83536/1-027M](#) [CX-4014](#) [MAHC-5494](#) [MAVCD-5419-6](#) [703XCX-120A](#) [7-1393100-5](#) [7-1393111-7](#)
[7-1393144-5](#) [7-1393767-8](#)