



BOARD-TO-BOARD JUMPERS & SHUNTS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

SHUNT, ECON, PHBR 15 AU, BLACK

AMP | Blank

382811-6

TE Internal Number: 382811-6

Always EU RoHS/ELV Compliant

Shunt Type **Economy**

Shunt Style **Open Top**

Centerline **2.54 mm [.1 in]**

Number of Positions **2**

Product Drawings

ECONOMY SHUNT ASSEMBLY

PDF
English

CAD Files

3D PDF

PDF
English

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

AMPMODU_INTERCONNECTION_SYSTEM_SECTION_6_7AND8

PDF
English

Product Specifications

Product Specification

CONNECTOR, LOW PROFILE ECONOMY & MULTI-POSITION SHUNT

PDF
English

Qualification Test Report

QUALIFICATION TEST REPORT, CONNECTOR, LOW PROFILE ECONOMY & MULTI POSITION SHUNT

TIF
English

QUALIFICATION TEST REPORT, CONNECTOR, LOW PROFILE ECONOMY & MULTI POSITION SHUNT

PDF
English

QUALIFICATION TEST REPORT, CONNECTOR, LOW PROFILE ECONOMY & MULTI POSITION SHUNT

PDF
Japanese

Product Environmental Compliance

TE Material Declaration

[MD_382811-6_05042015456_dmtec](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[Low Profile, Economy, And Dual Beam Shunt Connectors 382811, 390088, And 382823](#)

PDF
English

[Low Profile, Economy, And Dual Beam Shunt Connectors 382811, 390088, And 382823](#)

TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Profile	Low
	Product Type	Shunt
Configuration Features	Number of Positions	2
Electrical Characteristics	Insulation Resistance (MΩ)	1000
Body Features	Handle	Without
Contact Features	Shunt Type	Economy
	Shunt Style	Open Top
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness	.381 μm [15 μin]
	Contact Mating Area Plating Material	Gold
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Polyester - GF
	Housing Color	Black
Dimensions	Height	6.35 mm [.25 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Industry Standards	UL Rating	Recognized
	CSA Certified	Yes

UL Certified

100

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Method

Box

Packaging Quantity

1500

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

TRIMMERS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	PCB D-SUB CONNECTORS	RIBBON CABLE CONNECTORS
433PW 2K 404806505008	4P AMPMODU II STIFT LEI 826648-4	09 MSFL PLUG RA 318 (IN, FM, BL) 747840-3	10P, FOB, THT, MICRO- MATCH VALUE LINE 1-2178710-0
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [67230-005LF](#)