

Accessories and equipment for terminal blocks

Technical drawings of limit switches in ".dwg" format are available at www.pokoj.com.pl in the section Offer - Design materials.


DK/Z® type markers for terminal blocks

The DK/Z type markers are intended mainly for marking current lines of terminal blocks. The markers are available in white or yellow profile tapes with black print. The tape is perforated in equal L steps which enables tearing away single elements. The DK/Z type markers have IEC Standard Conformity Certificate. BBJ-SEP attestation and Polish Register of Shipping attestation, UL. The insulating material used conforms to 2002/95/EC.


The DK/Z-5 type markers are used for: ZUG, LZW, ZG-G, ZP, ZG, BM, OBL, LPI, ZUO, ZGO

The DK/Z-6 type markers are used for: ZUG (except for ZUG-2,5), ZP, ZG-G (except for ZG-2,5), LZW, BM, OBL, LPI, ZUO, ZGO

LOCATION OF MARKERS



DIMENSIONS OF PROFILED TAPE



Dimensions of the profile tape:
L=4,5 dla DK/Z-5
L=5,8 dla DK/Z-6



DK/Z-5 markers

TYPE	DK/Z-5	DK/Z-5	DK/Z-5
Catalogue number	51-72□□□	51-72□□□	51-72□□□
Colour	white ○	white ○	white ○
Print	"-.....0-" "/.....0/" ".....0:" "+.....0+ " ".....0," ".....0~ " ".....0." ".....0;" ".....0=" ".....MA	"L1".....L1 "L2".....L2 "L3".....L3 " L 1 , L 2 , L 3 " ".....L X " " P E " ".....P E " " P E N " ".....P P " " n o p r i n t "	"1...10".....D0 "11...20".....D1 "21...30".....D2 "31...40".....D3 "41...50".....D4 "51...60".....D5 "61...70".....D6 "71...80".....D7 "81...90".....D8 "91...100".....D9
Insulating material	self-extinguishing PVC	self-extinguishing PVC	self-extinguishing PVC
Ambient temperature	-30...+100°C	-30...+100°C	-30...+100°C
Package	250pcs.	250pcs.	250pcs.

DK/Z-6 markers

TYPE	DK/Z-6	DK/Z-6	DK/Z-6	DK/Z-6
Catalogue number	51-62□□□	51-62□□□	51-62□□□	51-62□□□
Colour	white ○	white ○	white ○	white ○
Print	"1...10".....D0 "11...20".....D1 "21...30".....D2 "31...40".....D3 "41...50".....D4 "51...60".....D5 "61...70".....D6 "71...80".....D7 "81...90".....D8 "91...100".....D9	"101...110".....H0 "111...120".....H1 "121...130".....H2 "131...140".....H3 "141...150".....H4 "151...160".....H5 "161...170".....H6 "171...180".....H7 "181...190".....H8 "191...200".....H9	"201...210".....S0 "211...220".....S1 "221...230".....S2 "231...240".....S3 "241...250".....S4 "251...260".....S5 "261...270".....S6 "271...280".....S7 "281...290".....S8 "291...300".....S9	"301...310".....T0 "311...320".....T1 "321...330".....T2 "331...340".....T3 "341...350".....T4 "351...360".....T5 "361...370".....T6 "371...380".....T7 "381...390".....T8 "391...400".....T9
Insulating material	self-extinguishing PVC	self-extinguishing PVC	self-extinguishing PVC	self-extinguishing PVC
Ambient temperature	-30...+100°C	-30...+100°C	-30...+100°C	-30...+100°C
Package	250pcs.	250pcs.	250pcs.	250pcs.