

9271 Twinax - Twinaxial Cable

		<p style="text-align: center;">For more information please call 1-800-Belden1</p> <p style="text-align: center;"><u>See Put-ups and Colors</u></p>
---	--	---

Description:

25 AWG stranded (7x33) tinned copper conductors, polyethylene insulation, Beldfoil® shield (100% coverage), stranded tinned copper drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	25
Stranding	7x33
Conductor Diameter	.021 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	PE - Polyethylene
Insulation Diameter	.083 in.

PAIR:

Pair Diameter	.170 in.
---------------	----------

Pair Color Code Chart :

Number	Color
1	Blue & Clear

OUTER SHIELD:

Outer Shield Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	7x30
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:



9271 Twinax - Twinaxial Cable

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.240 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
UL Temperature Rating	60°C (UL AWM Style 2092)
Bulk Cable Weight	25 lbs/1000 ft.
Max. Recommended Pulling Tension	17 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	UL Style 2092 (300 V 60°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

FLAME TEST:

UL Flame Test	UL1685 UL Loading
---------------	-------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	124 Ohms
Nom. Inductance	0.188 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	12.2 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	22.0 pF/ft
Nominal Velocity of Propagation	66 %
Nominal Delay	1.54 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	31.8 Ohms/1000 ft
Nominal Outer Shield DC Resistance	12 Ohms/1000 ft
Nom. Attenuation :	

9271 Twinax - Twinaxial Cable

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.6
	10			1.7
	50			3.6
	100			5.0
	200			6.9
	400			9.6

Max. Operating Voltage - UL 300 V RMS (UL AWM Style 2092)

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9271 006100	TW PR FS PVC	100	3.2	BLUE, LIGHT	
9271 0061000	TW PR FS PVC	1000	28	BLUE, LIGHT	C
9271 006500	TW PR FS PVC	500	12.5	BLUE, LIGHT	C
9271 006U1000	TW PR FS PVC	U1000	27	BLUE, LIGHT	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-09-2005

© 2006 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden CDT Electronics Division declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [belden](#) manufacturer:

Other Similar products are found below :

[HIPWP4LA](#) [HIPWP2LA](#) [49905A 060S2](#) [49907A 060S2](#) [9728 0601000](#) [8916-GRN/YEL-500](#) [8916-YEL-500](#) [8918-GRN/YEL-100](#) [8918-GRY-1000](#) [8919-DK-BLU-100](#) [8920-008-1000](#) [8920-BRN-1000](#) [8920-GRY-1000](#) [5T00UP 008500](#) [7810A-BLK-500](#) [7918A-BLK-1000](#) [7934A-BLK-1000](#) [7937A-BLK-1000](#) [8019-100](#) [8080](#) [8108-060-1000](#) [8125-CHR-100](#) [8132-CHR-1000](#) [8133-CHR-1000](#) [8155-CHR-1000](#) [8162-060-1000](#) [8162-CHR-1000](#) [8164-CHR-100](#) [8164-CHR-1000](#) [8185-CHR-100](#) [8205-CHR-1000](#) [8214-010-1000](#) [8221-BLK-1000](#) [8233-010-1000](#) [8233-BLK-1000](#) [8237-BLK-500](#) [8238-BLK-500](#) [8241-006-U1000](#) [8241A-BLK-1000](#) [8241F-RED-MATTE-1000](#) [8263-BLK-U1000](#) [8281-003-1000](#) [8281 010500](#) [83000 002100](#) [83002 0101000](#) [83003-006-500](#) [83003-VIO-500](#) [83004-RED-100](#) [83008 0091000](#) [83008-WHT-1000](#)