

This document was generated on 02/03/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0014600081

Status: Active

Overview: SL™ Modular Connectors

Description: 2.54mm Pitch SL™ Insulation Displacement Connector Assembly, Female, Single

Row, Version A, Non-polarized, Wire Size 24 AWG, 3.81µm Tin/Lead (SnPb), 8 Circuits

Documents:

3D Model Product Specification PS-70400 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Ribbon Cable / Wire Trap Connectors

Series 70400

Comments Terminals Preloaded

Component Type Housing Glow-Wire Compliant No

Overview <u>SLTM Modular Connectors</u>

Product Name SL™

UPC 800753765559

Physical

Circuits (Loaded) 8
Color - Resin Black
Durability (mating cycles max) 25
Entry Angle Vertical
Flammability 94V-0
Lock to Mating Part None

Material - Metal Phosphor Bronze

Material - Plating Mating Tin Material - Plating Termination Tin

Material - Resin Polyester Alloy

Number of Rows **PCB** Retention None Packaging Type Tube Pitch - Mating Interface 2.54mm Plating min - Mating 3.810µm Plating min - Termination 1.905um Polarized to Mating Part Nο Stackable Yes Surface Mount Compatible (SMC) N/A

Temperature Range - Operating -40°C to +105°C Termination Interface: Style IDT or Pierce Wire Insulation Diameter 1.35mm max.

Wire Size AWG 2

Wire/Cable Type Discrete Wire, Ribbon Cable


Electrical

Current - Maximum per Contact 3.0A Voltage - Maximum 250V

Material Info

Old Part Number 70400-0007

Reference - Drawing Numbers



Series image - Reference only

China RoHS

EU ELV

Not Reviewed

EU RoHS Not Reviewed

REACH SVHC Not Reviewed Halogen-Free

Status

Not Reviewed

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Not Reviewed ELV Not Reviewed

Search Parts in this Series

70400 Series

Mates With

Single Row Headers and Housings, $\underline{8624}$, 70203, 42375, 42377

Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product #

Product Specification Sales Drawing	PS-70400 SDA-70400-0001-0024	Hawk [™] Semi- <u>0623004900</u> Automatic Discrete Wire Terminator for Rebuilt CE Approved*	
		Hawk™ Flat Flex Cable Terminator with Break-off	0623005200
		Ribbon Cable Tool Kit, Press Not Included	0622016600
		Hawk™ Semi- Automatic Discrete Wire Terminator	0623003100
		Hawk™ Ribbon Cable Terminator without Break-off	0623003000
		Hawk™ Ribbon Cable Terminator with Break-off	0623005300
		IDT - Semi-automatic <u>0011200949</u>	

- Bench-Top Terminator

This document was generated on 02/03/2016
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF