

This document was generated on 02/28/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1704805022

Status: **Active**

Overview: Impact Backplane Connector and Cable Assembly System

Impact 85 Ohm Plus 5 Pair Right Angle Daughtercard, Right Guided, 12 Columns, 180 **Description:**

Circuits, Plated Through Hole Dimension 0.39mm, Lead Free

Documents:

Application Specification AS-76060-990-001 (PDF) 3D Model

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-170540-999-001 (PDF)

Agency Certification

E29179

General

Product Family Backplane Connectors

Series 170480

Application Conventional, Daughtercard

Application Tooling Documents TM-622018799 Component Type **PCB** Receptacle

Impact Backplane Connector and Cable Assembly Overview

System

Yes

None

Product Name Impact

UPC 884982710887

Physical

Keying to Mating Part

Circuits (Loaded) 180 Circuits (maximum) 180 Color - Resin Gray Durability (mating cycles max) 200 First Mate / Last Break Nο Flammability 94V-0 Guide to Mating Part

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination

Material - Resin High Temperature Thermoplastic

Net Weight 27.743/g Number of Columns 12 Number of Pairs 5 Number of Rows 15


Orientation Right Angle PC Tail Length 1.20mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.00mm Packaging Type Tray

Pitch - Mating Interface 1.35mm, 1.90mm Pitch - Termination Interface 1.35mm, 1.90mm

Plating min - Mating 0.762µm Polarized to PCB No Stackable Nο Surface Mount Compatible (SMC) No

Temperature Range - Operating -55°C to +85°C

Termination Interface: Style Through Hole - Compliant Pin



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant **REACH SVHC** Not Contained Per -ED/30/2017 (7 July 2017)

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS Green Image **ELV** Not Relevant **RoHS Phthalates** Not Contained

Search Parts in this Series

170480 Series

Mates With

170475 Impact 85 Ohm Plus Vertical Header

Electrical

Current - Maximum per Contact 0.75A
Data Rate 25.0 Gbps

 $\begin{array}{ll} \text{Impedance} & 85\Omega \\ \text{Shield Type} & \text{N/A} \\ \text{Shielded} & \text{No} \end{array}$

Voltage - Maximum 30V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers

Application Specification
Electrical Model Document
Product Specification
S-Parameter Model
Sales Drawing
Symbol/Footprint Data

AS-76060-990-001
EE-170480-0001
PS-170540-999-001
SP-170480-0003
SD-170480-0004
SYM-170480-5022

This document was generated on 02/28/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 532939-1 5-531355-3 5532901-3 85838-180LF HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7 77427-121LF