

Part Number: CXF 4/2







Family	inserts
Version	screw terminal connections
Series	CX
Product type	with female contacts
Model	female insert
Reference standard	EN 61984 (2001-11)
Contact type	silver plated
No. of poles	4 poles + 🕒
Auxiliaries poles	2 poles (16A max - 400V/6kV/3)
Voltage (V)	690V
Current (A)	80A (A.C./D.C.)
Wire section	4mm² - 16mm²
Awg size	12 - 6
Quality mark	71 ° 600V 66 0 6 0
IP degree of protection	IP20 degree of protection without enclosure; IP65, IP66, IP67, IP68 (EN 60529) and IP69K (DIN 40050 - 9) with enclosure
Fixing centre distance	size "77.27"
Impulse withstand voltage	8kV
Pollution degree	3
Barcode EAN13	8015747042338
Notes	CX 4/2 inserts:
	- characteristics according to EN 61984: (80A 690V 8kV 3)

The information and the dimensions contained are not binding and may be changed without prior notice.

The drawing's dimensions are in mm.

2 Auxiliary contacts:(16A 400V 6kV 3) 2 Auxiliary contacts:(16A 400/690V 6kV 2)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ilme manufacturer:

Other Similar products are found below:

CSHF 10 CZAP 25 L CDAF 16 CDSHF 18 CDSHF 42 N CHC 06 L CHI 06 LS CHO 16 L CK 03 CXAN CK 03 IAPS CK 03 VANS

CKA 03 C CKAX 03 IA TAPC 06 L25 CAOR 16.21 CAV 10.21 CDSHF 27 N CDSHM 27 N CDSHM 42 N CDSM 42 CHI 16 CHV 10

CK 03 CAN CK 03 CN CK 03 VAS CKA 03 I CKA 03 IA CKAX 03 CX CNEM 24 T TAPC 10.25 TAPH 16.32 TAPW 06 L25

PE3264SV PE1664SV CXM4/0 CAV 06 LG21 CHP 06 L COB 06 CMS CHP 48 LS PEW3265PV CQEM18 CCPZTP CHV 06 L16

CZIR 06 L TAPH 16.40 CHP 06 LS2 TAPC 24.32 TAVH 10 G32 THCH 06 LG THIW 10