





CIRCUIT DIAGRAM



P.C.B. LAND DIMENSION

Rating	DC12V 0.5A	Operation force	130±30gf
Insulation resistance	≥100MΩ	Free position	5.0±0.3mm
Contact Resistance	≤100mΩ (MAX)	Travel	0.25 <sup>+0.25</sup> <sub>-0.1</sub> mm
Soldering temper	245°C±5°C 3 Sec.	Temperature range	-20°~+70°C
Mechanical life	100,000 cycles	Moisture resistance	60°±2°C, 90~95% RH
Electrical life	50,000 cycles		

Case	Stanyl
Stem	Stanyl
Terminal	C2680R-EH (Ag 0.5u)
Cover	SUS 301
C/PLATE	SUS 304

REVISION	DESCRIPTION	REVISED BY	TOLERANCES X±	ANGLE 1/2°	UNIT mm	PART NAME	DTSM SPEC DRAWING	DWG NO
△								WS0132A
△								
△								
△								
△	2005.08.26 更新圖框 發圖	吳美玉					DTSM-32N	



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Tactile Switches](#) category:*

*Click to view products by [Canal](#) manufacturer:*

Other Similar products are found below :

[KMR633NG LFG](#) [5GTH9202242](#) [6426-201-11343](#) [MJ1226](#) [MJTP1109B](#) [MJTP1138EAUTR](#) [MJTP1230BL](#) [MJTPSHW](#) [GS6.90F300QP](#) [1-1977223-0](#) [1-1977120-4](#) [ADTSA62NV](#) [ADTSA62RV](#) [ADTSA63KV](#) [ADTSA644NV](#) [ADTSM24NVTR](#) [ADTSMW66NV](#) [ADTSMW67RV](#) [ATM533VTR](#) [1571300-3](#) [B3F-3123](#) [B3F-6055A](#) [B3F-B32-01-KIT](#) [1977177-8](#) [1977266-1](#) [2-1977223-4](#) [2-1977223-7](#) [ADTS644KV](#) [ADTSA61RV](#) [ADTSA62KV](#) [ADTSA63NV](#) [ADTSA63RV](#) [ADTSA65NV](#) [ADTSM21NSVTR](#) [ADTSM25RVTR](#) [ADTSM31RVTR](#) [ADTSM32NVTR](#) [ADTSM61YVTR](#) [ADTSM63SVTR](#) [ADTSM644KVTR](#) [ADTSMW64RV](#) [ADTSMW69NV](#) [FSMRA4JHA04](#) [GS4.70F300QP](#) [D38999/20JJ37SA](#) [TL1105B](#) [TL1105J](#) [ATH447K2Q](#) [ATM534VTR](#) [MJ1215](#)