TOSHIBA Photocoupler GaAłAs IRED + Photo IC

# TLP701F

### Industrial Inverters Inverter for Air Conditioners IGBT/Power MOSFET Gate Drive

TLP701F consists of a GaAłAs light-emitting diode and an integrated photodetector.

This unit is 6-lead SDIP package. The TLP701F is 50% smaller than the 8-pin DIP and meets the reinforced insulation class requirements of international safety standards. Therefore the mounting area can be reduced in equipment requiring safety standard certification.

The TLP701F is suitable for gate driving circuits for IGBTs or power MOSFETs. In particular, the TLP701F is capable of "direct" gate driving of low-power IGBTs.

Absolute Maximum ratings and electrical characteristics are the same as The TLP701 technical data sheets.

- Peak output current : ±0.6 A (max)
- Guaranteed performance over temperature : −40 to 100°C
- Supply current
- Power supply voltage
- Threshold input current
- Switching time (t<sub>pLH</sub> / t<sub>pHL</sub>)
- Common mode transient immunity
- Isolation voltage
- Construction mechanical rating

Creepage Distance Clearance	8.0 mm (min) 8.0 mm (min)
Insulation Thickness	0.4 mm (min)

- UL Recognized
- Option (D4)
  - TÜV approved

: UL1577, File No. E67349

: 2 mA (max)

: 700 ns (max)

 $: I_{FLH} = 5 \text{ mA} (\text{max})$ 

: ±10 kV/µs (min)

: 5000 Vrms (min)

: 10 to 30 V

: 8000 Vpk


: EN60747-5-2 Certificate No. R50033433 : 1140 Vpk

Maximum operating insulation voltage Highest permissible over voltage


(Note) When an EN60747-5-2 approved type is needed, please designate the "Option(D4)"

#### Truth Table

Input	LED	Tr1	Tr2	Output
Н	ON	ON	OFF	Н
L	OFF	OFF	ON	L




Weight: 0.26 g (typ.)



Pin Configuration (Top View)

1: ANODE 2: NC 3: CATHODE 4: GND 5: V<sub>O</sub> (OUTPUT) 6: V<sub>CC</sub>



A  $0.1\mathchar`-\mu F$  bypass capacitor must be connected between pins 6 and 4. (See Note 6.)

Unit in mm

## **RESTRICTIONS ON PRODUCT USE**

- Toshiba Corporation, and its subsidiaries and affiliates (collectively "TOSHIBA"), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively "Product") without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before creating and producing designs and using, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application that Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.
- Product is intended for use in general electronics applications (e.g., computers, personal equipment, office equipment, measuring equipment, industrial robots and home electronics appliances) or for specific applications as expressly stated in this document. Product is neither intended nor warranted for use in equipment or systems that require extraordinarily high levels of quality and/or reliability and/or a malfunction or failure of which may cause loss of human life, bodily injury, serious property damage or serious public impact ("Unintended Use"). Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. Do not use Product for Unintended Use unless specifically permitted in this document.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.
- GaAs (Gallium Arsenide) is used in Product. GaAs is harmful to humans if consumed or absorbed, whether in the form of dust or vapor. Handle with care and do not break, cut, crush, grind, dissolve chemically or otherwise expose GaAs in Product.
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without
  limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile
  technology products (mass destruction weapons). Product and related software and technology may be controlled under the
  Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product
  or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. TOSHIBA assumes no liability for damages or losses occurring as a result of noncompliance with applicable laws and regulations.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Logic Output Optocouplers category:

Click to view products by Toshiba manufacturer:

Other Similar products are found below :

ACPL-K370-500E ACPL-P340-500E ACPL-P341-500E ACPL-36JV-000E H11L1S(TA)-V CPC1590P TLP700H(F) TLP705A(F) TLP152(E TLP700A(F) FOD3150 ACPL-K376-500E ACPL-K376-560E VO3120-X001 ACPL-M483-500E TLP705A(TP,F) ACNW3410-000E VO3120-X019T TLP700A(TP,F) ACPL-32JT-500E ACPL-W483-500E ACPL-W483-560E TLP701H(TP,F) ACPL-W340-560E H11L2S(TA)-V H11L3SR2M HCNW4506 HCPL-315J HCPL3700SD HCPL-4200-500E HCPL-5301 HCPL-5700#300 HCPL-5701 HCPL-6731 HCPL-6750 HCPL-T251-000E TLP151A(E) TLP2345(E(T TLP2348(E(T TLP350H(F) TLP5214(E(O TLP701AF(F) MID400 6N140A 8302401EA 8302401EC FOD8333 TLP351H(F) 5962-8947701PA 5962-89785022A