

This document was generated on 02/07/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>1705251807</u>

Status: Active

Overview: Impact Backplane Connector and Cable Assembly System

Description: Impact 85 Ohm Plus 3 Pair Vertical Backplane Header, Unguided, Open Endwalls, 8

Columns, 72 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm,

Lead Free

Documents:

<u>3D Model</u> <u>Application Specification AS-76060-990-001 (PDF)</u>
Drawing (PDF) Packaging Specification PK-70873-7700 (PDF)

Product Specification PS-170540-999-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL E29179

General

Product Family Backplane Connectors

Series 170525
Application Conventional
Application Tooling Documents TM-622018799
Component Type PCB Header

Overview <u>Impact Backplane Connector and Cable Assembly</u>

System Impact

UPC 884982465039

Physical

Product Name

Circuits (Loaded) 72
Circuits (maximum) 72
Color - Resin Gray
Durability (mating cycles max) 200
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part No
Keying to Mating Part None

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic


Net Weight 2.223/g Number of Columns Number of Pairs 3 Number of Rows Orientation Vertical PC Tail Length 1.40mm PCB Locator Nο **PCB** Retention None PCB Thickness - Recommended 1.00mm Packaging Type Tray

Pitch - Mating Interface 1.35mm, 1.90mm Pitch - Termination Interface 1.35mm, 1.90mm

 $\begin{array}{ll} \text{Plating min - Mating} & 0.762 \mu\text{m} \\ \text{Polarized to PCB} & \text{No} \\ \text{Stackable} & \text{No} \\ \text{Surface Mount Compatible (SMC)} & \text{No} \\ \end{array}$

Temperature Range - Operating -55°C to +85°C

Termination Interface: Style Through Hole - Compliant Pin



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per -ED/30/2017 (7 July 2017)

Halogen-Free Status Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

170525 Series

Mates With

170530 Impact 85 Ohm Plus Right Angle

Receptacle

Electrical

Current - Maximum per Contact 0.75A Data Rate 25.0 Gbps

Impedance 85Ω N/A Shield Type Shielded No

Voltage - Maximum 30V AC (RMS)/DC

Solder Process Data

Lead-freeProcess Capability N/A

Material Info

Reference - Drawing Numbers Application Specification AS-76060-990-001 **Packaging Specification** PK-70873-7700 **Product Specification** PS-170540-999-001 Sales Drawing SD-170525-0001-001 Symbol/Footprint Data SYM-170525-1807

This document was generated on 02/07/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for High Speed/Modular Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

2332816-1 89006-1137LF 650827-1 65762-001LF 73474-201LF 74040-1346 74075-0267 1410191-1 1410337-1 1410368-3 1410964-2 1410367-3 1410971-4 1467833-1 2000877-1 2000878-1 2041314-1 2065387-1 2187307-1 2187462-1 2226278-6 KA81-07 91290-101LF 163P 1934290-1 2000875-1 2065917-1 2102736-2 FSR-40 2169868-2 2226279-2 22354-8 437-5040-000 5-1393565-0 532449-3 532803-2 34745-0001 0736440217 1-1393708-5 72388-0021LF 73774-1000 532939-1 5-531355-3 5532901-3 85838-180LF HM1S43TRR460H6PLF 0760205010 1-966831-4 3-1469268-7 77427-121LF