



SPECIFICATION

Part Numbers: R24Color-0100/1000 ROLLS
For Cut/Strip/Wrap Applications

This specification is for wire per UL Style 1422, 105°C, no voltage rated, 24 AWG. Solid silver plated oxygen free copper.

CONDUCTOR:

Size:	24 AWG. Solid	Circular Mil Area:	394 Minimum
Material:	Silver plated oxygen free, high Conductivity copper per ASTM-B 170 Grade.	DC Resistance.:	@20°C(68°F) max. 26.2 Ω/M:
Plating:	Silver, 40 micro-inch minimum per ASTM-B 298.	Elongation:	20% before insulation
		Weight:	1.22 lbs./ M
		Diameter:	0.0201" nom. 0.0200" min.

INSULATION:

Material:	Kynar 460	Diameter:	0.0310" ± .0015"
Min. Avg. Wall:	0.005"	Spark Test:	2,000VAC RMS
Min. any. Pt.:	0.004"	Weight:	0.297 lbs./M
Color:	As specified	Total Weight:	1.55 lbs./M
Flammability	VW-1		



SPECIFICATION

Part Numbers: R26Color-0100/1000 ROLLS

This specification is for wire per UL Style 1422, 105°C, no voltage rated, 26 AWG. Solid silver plated oxygen free copper.

CONDUCTOR:

Size:	26 AWG. Solid	Circular Mil Area:	246 Minimum
Material:	Silver plated oxygen free, high Conductivity copper per ASTM-B 170 Grade.	DC Resistance.:	@20°C(68°F) max. 43.53 Ω/M:
Plating:	Silver, 40 micro-inch minimum per ASTM-B 298.	Elongation:	20% before insulation
		Weight:	0.765 lbs./ M
		Diameter:	0.0159" nom. 0.0158" min.

INSULATION:

Material:	Kynar 460	Diameter:	0.0270" ± .0015"
Min. Avg. Wall:	0.005"	Spark Test:	2,000 VAC RMS
Min. any. Pt.:	0.004"	Weight:	0.285 lbs./M
Color:	As specified	Total Weight:	1.05 lbs./M
Flammability	VW-1		

**SPECIFICATION**

Part Numbers: R28Color-0100/100 foot ROLLS

This specification is for wire per UL Style 1422, 105°C, no voltage rated, 28 AWG. Solid silver plated oxygen free copper.

CONDUCTOR:

Size:	28 AWG. Solid	Circular Mil Area:	154 Minimum
Material:	Silver plated oxygen free, high Conductivity copper per ASTM-B 170 Grade.	DC Resistance.:	@20°C(68°F) max. 66.8 Ω/M:
Plating:	Silver, 40 micro-inch minimum per ASTM-B 298.	Elongation:	20% before insulation
		Weight:	0.48 lbs./ M
		Diameter:	0.0126" nom. 0.0125" min.

INSULATION:

Material:	Kynar 460	Diameter:	0.0240" ± .001"
Min. Avg. Wall:	0.005"	Spark Test:	2,000 VAC RMS
Min. any. Pt.:	0.004"	Weight:	0.250 lbs./M
Color:	As specified	Total Weight:	0.73 lbs./M
Flammability	VW-1		

**SPECIFICATION**

Part Numbers: R30Color-0100/1000 ROLLS, Also Pre-Stripped/Pre-Cut Packs
For Cut/Strip/Wrap Applications

This specification is for wire per UL Style 1423, 105°C, no voltage rated, 30 AWG. Solid silver-plated oxygen free copper.

CONDUCTOR:

Size:	30 AWG. Solid	Circular Mil Area:	96 Minimum
Material:	Silver plated oxygen free, high Conductivity copper per ASTM-B 170 Grade.	DC Resistance.:	@20°C(68°F) max. 110.09 Ω/M:
Plating:	Silver, 40 micro-inch minimum per ASTM-B 298.	Elongation:	20% before insulation
		Weight:	0.0303 lbs./ M
		Diameter:	0.0100" nom. 0.0099"min.

INSULATION:

Material:	Kynar 460	Diameter:	0.0195" ± .0010"
Min. Avg. Wall:	0.004"	Spark Test:	2,000VAC RMS
Min. any. Pt.:	0.003"	Weight:	0.168 lbs./M
Color:	As specified	Total Weight:	0.47 lbs./M
Flammability	VW-1		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialised Cables category](#):

Click to view products by [OK Industries manufacturer](#):

Other Similar products are found below :

[GP-IE515546DS-002](#) [96CB-L2020PIB2](#) [1200740161](#) [R7ACAB003S](#) [R88ACAKA0015SRE](#) [R88ACAWL005SDE](#) [R88ACRGB010C](#)
[R88ACRGD0R3C](#) [R88ACRGD0R3CBS](#) [R88ACRKA020CRE](#) [1300660201](#) [1971465-2](#) [22733-8](#) [2R7004A20F060](#) [SSL009PC2DC012N](#)
[FC2A-KC6C](#) [FZVS415M](#) [CCSFCBF2](#) [R7ACAB005S](#) [R88ACAGD003SRE](#) [R88ACAGE005BRE](#) [R88ACAKE003SRE](#) [R88ACAKE005SRE](#)
[R88ACAKE010SRE](#) [R88ACRKM010SRE](#) [R88AFIK222RE](#) [XS2WM12PUR4SA10M](#) [XS2WM12PVC4SA10M](#) [05AU05](#) [UCABLE](#)
[10114734-2010LF](#) [R88ACRKC015NRE](#) [XW2Z010H3](#) [XW2Z010H1](#) [5-1589827-8](#) [861084-1](#) [XW2Z200JB24](#) [CR4000A76M020](#)
[1300140039](#) [CR4000A76M005](#) [CR4006A76M005](#) [10077488-N0550FDLF](#) [XW2ZRY150C](#) [I4JPBJLUXX100](#) [I4JPBJLUXX50](#) [CM06W](#)
[CM08](#) [POE004](#) [0243 009 05](#) [0243 009 20](#)