


G6A

Low Signal Relay

World's Standard Model G6A!

- Resistant to electromagnetic interference, enables high-density mounting.
- Impulse withstand voltage of 1,500V meets FCC requirements.
- Gold-clad twin-contacts provide short contact bounce in addition to its high contact reliability.
- A variety of products that cover a wide range of use.

RoHS Compliant



Model Number Legend

G6A \square - \square \square \square \square - \square - \square
 1 2 3 4 5 6 7

1. Relay Function

- None : Single-side stable
- U : Single-winding latching
- K : Double-winding latching

2. Contact Form

2: DPDT (2c)

3. Contact Type

7: Bifurcated crossbar Ag (Au-Alloy)

4. Protective Structure

4: Fully sealed

5. Terminal Shape

P: PCB Terminals

6. Classification

- None : Standard
- LT : Low thermoelectromotive force
- ST : Stand-off 0.64 mm
- 15 : High-sensitivity (150 mW)
- 40 : Low-sensitivity
(Single-side Stable: 400 mW
Double-winding Latching: 300 mW)

7. Approved Standards

- None : Standard
- US : UL, CSA

Application Examples

- Telecommunication equipment
- Security equipment
- Medical equipment
- Test & measurement equipment

G
6
A

Ordering Information

UL, CSA Certified Models

Relay Function	Classification	Contact form	Model	Rated coil voltage (VDC)	Minimum packing unit
Single-side Stable Type	Standard	DPDT (2c)	G6A-274P-ST-US	3, 4.5, 5, 6, 9, 12, 24 48	25 pcs/tube
	Low-sensitivity		G6A-274P-ST40-US	3, 5, 6, 9, 12, 24 48	
	High-sensitivity		G6A-274P-ST15-US	3, 5, 6, 9, 12, 24 48	
Single-winding Latching Type	Standard		G6AU-274P-ST-US	3, 4.5, 5, 6, 9, 12, 24 48	
	Standard		G6AK-274P-ST-US	3, 4.5, 5, 6, 9, 12, 24 48	
Double-winding Latching Type	Low-sensitivity		G6AK-274P-ST40-US	3, 5, 6, 9, 12, 24 48	

Note: When ordering, add the rated coil voltage to the model number.

Example: G6A-274P-ST-US 3 VDC

\square Rated coil voltage

■ Ratings

● Coil: Single-side Stable (Standard Models)

Contact form	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Must operate voltage (V)	Must release voltage (V)	Max. voltage (V)	Power consumption (mW)
				% of rated voltage			
DPDT (2c)	3 VDC	66.7	45	70% max.	10% min.	200% (at 23°C)	Approx. 200
	4.5 VDC	44.6	101				
	5 VDC	40.0	125				
	6 VDC	33.3	180				
	9 VDC	22.2	405				
	12 VDC	16.7	720				
	24 VDC	8.3	2,880				
48 VDC	4.9	9,750	Approx. 235				

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.
 2. Operating characteristics are measured at a coil temperature of 23°C.
 3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

● Coil: Single-side Stable (Low-sensitivity Models)

Contact form	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Must operate voltage (V)	Must release voltage (V)	Max. voltage (V)	Power consumption (mW)
				% of rated voltage			
DPDT (2c)	3 VDC	133.3	22.5	70% max.	10% min.	150% (at 23°C)	Approx. 400
	5 VDC	80	62.5				
	6 VDC	66.7	90				
	9 VDC	44.3	203				
	12 VDC	33.3	360				
	24 VDC	16.7	1,440				
	48 VDC	8.3	5,760				

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.
 2. Operating characteristics are measured at a coil temperature of 23°C.
 3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

● Coil: Single-side Stable (High-sensitivity Models) (Low Thermoelectromotive Force)

Contact form	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Must operate voltage (V)	Must release voltage (V)	Max. voltage (V)	Power consumption (mW)
				% of rated voltage			
DPDT (2c)	3 VDC	50	60	80% max.	10% min.	200% (at 23°C)	Approx. 150
	4.5 VDC	33.3	135				
	5 VDC	30	167				
	6 VDC	25	240				
	9 VDC	16.7	540				
	12 VDC	12.5	960				
	24 VDC	6.3	3,840				
48 VDC	3.2	15,000					

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.
 2. Operating characteristics are measured at a coil temperature of 23°C.
 3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

● Coil: Single-winding Latching

Contact form	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Set voltage (V)	Reset voltage (V)	Max. voltage (V)	Power consumption (mW)
				% of rated voltage			
DPDT (2c)	3 VDC	33.7	89	70% max.	70% max.	200% (at 23°C)	Approx. 100
	5 VDC	20	250				
	6 VDC	16.7	360				
	9 VDC	11.1	810				
	12 VDC	8.3	1,440				
	24 VDC	4.2	5,760				
	48 VDC	2.5	19,000				Approx. 120

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.
 2. Operating characteristics are measured at a coil temperature of 23°C.
 3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

●Coil: Double-winding Latching (Standard Models)

Contact form	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Set voltage (V)	Reset voltage (V)	Max. voltage (V)	Power consumption (mW)
				% of rated voltage			
DPDT (2c)	3 VDC	66.7	45	70% max.	70% max.	200% (at 23°C)	Approx. 200
	4.5 VDC	40.2	112				Approx. 180
	5 VDC	36	139				
	6 VDC	30	200				
	9 VDC	20	450				
	12 VDC	15	800				
	24 VDC	7.5	3,200				
	48 VDC	4.2	11,520				Approx. 200

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.

2. Operating characteristics are measured at a coil temperature of 23°C.

3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

●Coil: Double-winding Latching (Low-sensitivity Models)

Contact form	Rated voltage	Rated current (mA)	Coil resistance (Ω)	Set voltage (V)	Reset voltage (V)	Max. voltage (V)	Power consumption (mW)
				% of rated voltage			
DPDT (2c)	3 VDC	120	25	70% max.	70% max.	150% (at 23°C)	Approx. 360
	4.5 VDC	79.9	56.3				
	5 VDC	72.5	69				
	6 VDC	60	100				
	9 VDC	40	225				
	12 VDC	30	400				
	24 VDC	15	1,600				
	48 VDC	7.5	6,400				

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.

2. Operating characteristics are measured at a coil temperature of 23°C.

3. The maximum voltage is the highest voltage that can be imposed on the relay coil.

●Contacts

Item	Load	
	Resistive load	Inductive load ($\cos\phi = 0.4;$ $L/R = 7 \text{ ms}$)
Contact type	Bifurcated crossbar	
Contact material	Ag (Au-Alloy) contact	
Rated load	0.5 A at 125 VAC; 2 A at 30 VDC	0.3 A at 125 VAC; 1 A at 30 VDC
Rated carry current	3 A	
Max. switching voltage	250 VAC, 220 VDC	
Max. switching current	2 A	1 A

■ Characteristics


Item	Classification	Single-side Stable	Single-winding Latching	Double-winding Latching
Contact resistance *1		50 mΩ max.		
Operate (set) time		5 ms max.	5 ms max.	
Release (reset) time		3 ms max.	5 ms max.	
Min. set/reset signal width		–	10 ms	
Insulation resistance *2		1,000 MΩ min. (at 500 VDC); except for set-reset		
Dielectric strength	Between coil and contacts	1,000 VAC, 50/60 Hz for 1 min		
	Between contacts of the same polarity	1,000 VAC, 50/60 Hz for 1 min		
	Between contacts of different polarity	1,000 VAC, 50/60 Hz for 1 min		
	Between set and reset coils	–	–	250 VAC, 50/60 Hz for 1 min
Impulse withstand voltage		1,500 V (10 × 160 μs) (conforms to FCC Part 68)		
Vibration resistance	Destruction	10 to 55 to 10 Hz, 2.5 mm single amplitude (5 mm double amplitude)		
	Malfunction	10 to 55 to 10 Hz, 1.65 mm single amplitude (3.3 mm double amplitude)		
Shock resistance	Destruction	1,000 m/s ²		
	Malfunction	500 m/s ²	300 m/s ²	
Durability	Mechanical	100,000,000 operations min. (at 36,000 operations/hr)		
	Electrical	500,000 operations min. (at 1,800 operations/hr)		
Failure rate (P level) *3		10 μA at 10 m VDC		
Ambient operating temperature		-40°C to 70°C (with no icing or no condensation)		
Ambient operating humidity		5% to 85%		
Weight		Approx. 3.5 g		

Note: The data shown above are initial values.


- *1. The contact resistance was measured with 10 mA at 1 VDC with a voltage drop method.
- *2. The insulation resistance was measured with a 500 VDC megohmmeter applied to the same parts as those used for checking the dielectric strength (except between the set and reset coil).
- *3. This value was measured at a switching frequency of 60 operations/min. This value may vary, depending on switching frequency, operating conditions, expected reliability level of the relay, etc. It is always recommended to double-check relay suitability under actual load conditions.

Engineering Data


Maximum Switching Power




Durability



Ambient Temperature vs. Maximum Coil Voltage




Ambient Temperature vs. Must Operate or Must Release Voltage




Note: "Maximum voltage" is the maximum voltage that can be applied to the Relay coil.

Shock Malfunction

G6A-274P




G6AK-274P




Test Conditions: Shock is applied in ±X, ±Y, and ±Z directions three times each with and without energizing the Relays to check the number of contact malfunctions.

●Electrical Durability Test *1



●Contact Reliability Test *1, *2




*1. The tests were conducted at an ambient temperature of 23°C.

*2. The contact resistance data are periodically measured reference values and are not values from each monitoring operation. Contact resistance values will vary according to the switching frequency and operating environment, so be sure to check operation under the actual operating conditions before use.


●Mutual Magnetic Interference

G6A-274P

G6A




G6A-274P



●External Magnetic Interference


G6AK-274P

(Average value)




G6AK-274P

(Average value)




G6AK-274P

(Average value)




●Time distribution of Operating and Release/Set and Reset *1

G6A-274P




G6AK-274P




●Bounce Time distribution of Operating and Release/Set and Reset *1

G6A-274P




G6AK-274P



●High-frequency Characteristics

• Measurement Conditions




Terminals which were not being measured were terminated with 50 Ω.
Measuring impedance: 50 Ω

Note: The high-frequency characteristics data were measured using a dedicated circuit board and actual values will vary depending on the usage conditions. Check the characteristics of the actual equipment being used.

●High-frequency Characteristics

(Isolation) *1, *2


(Average value (initial))



●High-frequency Characteristics

(Insertion Loss) *1, *2


(Average value (initial))



●High-frequency Characteristics

(Return Loss, V.SWR) *1, *2

(Average value (initial))





*1. The tests were conducted at an ambient temperature of 23°C.


*2. High-frequency characteristics depend on the PCB to which the Relay is mounted. Always check these characteristics, including durability, in the actual machine before use.

■Dimensions


Single-side stable G6A-274P





PCB Mounting Holes (BOTTOM VIEW) Tolerance: ±0.1




Terminal Arrangement/ Internal Connections (BOTTOM VIEW)




Single-winding latching G6AU-274P





PCB Mounting Holes (BOTTOM VIEW) Tolerance: ±0.1




Terminal Arrangement/ Internal Connections (BOTTOM VIEW)




Double-winding latching G6AK-274P



PCB Mounting Holes (BOTTOM VIEW) Tolerance: ±0.1



Terminal Arrangement/ Internal Connections (BOTTOM VIEW)



■Approved Standards

A variety of UL/CSA approved models are available. Note that the ratings are different from the domestic standard products. Make sure to clearly indicate "OO standard approved model" when ordering.

UL Recognized:  (File No. E41515)

CSA Certified:  (File No. LR31928)

Classification	Contact form	Coil ratings	Model	Contact ratings	Number of test operations
Single-side stable	DPDT (2c)	3 to 48 VDC	G6A-274P-ST-US	0.6 A, 125 VAC at 40°C 2 A, 30 VAC at 40°C 0.6 A, 110 VAC at 40°C	6,000
Latching			G6AK-274P-ST-US		
Low-sensitivity			G6A(K)-274P-ST40-US		
High-sensitivity			G6A-274P-ST15-US		

■Precautions

●Please refer to “PCB Relays Common Precautions” for correct use.

Correct Use

●Long-term Continuously ON Contacts

Using the Relay in a circuit where the Relay will be ON continuously for long periods (without switching) can lead to unstable contacts because the heat generated by the coil itself will affect the insulation, causing a film to develop on the contact surfaces. We recommend using a latching relay (magnetic-holding relay) in this kind of circuit. If a single-side stable model must be used in this kind of circuit, we recommend using a fail-safe circuit design that provides protection against contact failure or coil burnout.


●Relay Handling

When washing the product after soldering the Relay to a PCB, use a water-based solvent or alcohol-based solvent, and keep the solvent temperature to less than 40°C. Do not put the Relay in a cold cleaning bath immediately after soldering.

●Double-switching load in two poles

Double-switching in two poles as shown in the figure below, one pole and two pole interval may become MBB (Make Before Break) mechanically according to the timing of the point of contact switching (By the short-circuit mode), and the malfunction might be caused.

In such a circuit, direct electric switching should be avoided, and concern for contact to be carried after the contact of Relay absolutely switches in condition of no load.



- Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
- Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Low Signal Relays - PCB category](#):

Click to view products by [Omron manufacturer](#):

Other Similar products are found below :

[6-1393813-4](#) [6-1462039-0](#) [6-1617529-6](#) [617-12](#) [67RPCX-3](#) [7-1393809-0](#) [7-1393813-3](#) [7556072001](#) [80.010.4522.1](#) [FTR-B4GA006Z](#)
[FW1210S02](#) [9-1393813-6](#) [9-1617519-3](#) [9-1617582-5](#) [G6AK-2-H-DC5](#) [A-1.5W-K](#) [DF2E-L2-DC3V](#) [DS1EM24J](#) [DS1EM5J](#) [DS1ES5J](#) [DS4E-](#)
[M-DC5V-H48](#) [EC2-4.5TNJ](#) [EC2-9NJ](#) [B07B939BC1-0868](#) [1608043-4](#) [1617076-5](#) [1617117-3](#) [1617137-2](#) [1617518-5](#) [1617560](#)
[HMB1130K00](#) [HMB1131S06](#) [HMS1119S01](#) [HMS1131S10](#) [HMS1201S03](#) [HMS1201S87](#) [HMS1205S02](#) [2-1393807-6](#) [2-1617071-2](#) [2-](#)
[1617594-1](#) [JMGSC-5LW](#) [K6-PS](#) [KHS-17D11-110](#) [9-1393761-0](#) [9-1617352-3](#) [9-1617583-1](#) [276XAXH-9D](#) [1617072-3](#) [1617075-4](#) [1617109-](#)