



Switch-Hitter™

Constant Current LED Driver

**Model Number
AC-150CD3.0UVTS**


Input Voltage: 120-277V
Input Frequency: 50/60Hz
Side Mount/Leads

MULTI-CURRENT SWITCHING AND DIMMING

ELECTRICAL SPECIFICATIONS:


| Output Power Max. | Input Power | Input Current | Minimum PF (full load) | Max. THD (full load) | Output Voltage | Output Current | T case Max. | Minimum Starting Temp. | Efficiency Up To | Dimming Protocol | Dimming Range |
|-------------------|-------------|------------------------------|------------------------|----------------------|----------------|----------------|-------------|------------------------|------------------|------------------|---------------|
| 150W | 170W | 1.45A @ 120V 0.64A @ 277V | >0.95 | <20% | 30-50V | 3000mA±5% | 90° C | -40° C | 87% | 0 to 10V | 10 to 100% |
| 100W | 115W | 0.93A @ 120V 0.4A @ 277V | >0.95 | <20% | 30-50V | 2000mA±5% | 90° C | -40° C | 86% | 0 to 10V | 10 to 100% |
| 50W | 60W | 0.5A @ 120V 0.22A @ 277V | >0.95 | <20% | 30-50V | 1000mA±5% | 90° C | -40° C | 85% | 0 to 10V | 10 to 100% |

WIRING:



| Lead Lengths | | | | | |
|--------------|------|------|------|--------|------|
| Black | 5.9" | Blue | 5.9" | Purple | 5.9" |
| White | 5.9" | Red | 5.9" | Gray | 5.9" |

PHYSICAL:



| Dimensions | |
|-----------------|---------|
| Length | 9.5" |
| Width | 2.64" |
| Height | 1.6" |
| Mounting Length | 8.9" |
| Weight | xx lbs. |
| Case Qty. | xx pcs. |

SAFETY & PERFORMANCE:

- UL and cUL Recognized
- UL Outdoor Type I
- Class A sound rating
- No PCBs
- IP66
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 years based on max case temp of 90°C*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (2 KV)

INSTALLATION:

- LED drivers shall be installed inside UL approved electrical enclosures
- 18 AWG 600V/105C tinned strand copper lead-wires are required for installation
- Max Remote installation distance is 18 ft
- LED driver cases shall be grounded



*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See aceleds.com for complete warranty policy.



3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Gate Drivers](#) category:

Click to view products by [AC Electronics](#) manufacturer:

Other Similar products are found below :

[00028](#) [00053P0231](#) [8967380000](#) [56956](#) [CR7E-30DB-3.96E\(72\)](#) [57.404.7355.5](#) [LT4936](#) [57.904.0755.0](#) [5801-0903](#) [5803-0901](#) [5811-0902](#)
[5813-0901](#) [58410](#) [00576P0030](#) [00581P0070](#) [5882900001](#) [00103P0020](#) [00600P0005](#) [00-9050-LRPP](#) [00-9090-RDPP](#) [5951900000](#) [01-](#)
[1003W-10/32-15](#) [LTI LA6E-1S-WH-RC-FN12VXCR1](#) [0131700000](#) [00-2240](#) [LTP70N06](#) [LVP640](#) [0158-624-00](#) [5J0-1000LG-SIL](#) [020017-13](#)
[LY1D-2-5S-AC120](#) [LY2-0-US-AC120](#) [LY2-US-AC240](#) [LY3-UA-DC24](#) [00-5150](#) [00576P0020](#) [00600P0010](#) [LZNQ2M-US-DC5](#) [LZNQ2-](#)
[US-DC12](#) [LZP40N10](#) [00-8196-RDPP](#) [00-8274-RDPP](#) [00-8275-RDNP](#) [00-8609-RDPP](#) [00-8722-RDPP](#) [00-8728-WHPP](#) [00-8869-RDPP](#) [00-](#)
[9051-RDPP](#) [00-9091-LRPP](#) [00-9291-RDPP](#)