

This document was generated on 03/27/2015

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 22-16-2181

Status: Active

Overview: KK® Interconnect System - Molex

Description: KK® 254 PC Board Connector, Right Angle, End-to-End Stackable, 0.50µm Gold (Au),

18 Circuits

**Documents:** 

3D ModelProduct Specification PS-10-07 (PDF)Drawing (PDF)RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family PCB Receptacles

Series 4455

Application Board-to-Board, Signal

Overview KK® Interconnect System - Molex

Product Name KK® 254 UPC 800753737723

**Physical** 

Circuits (Loaded) 18
Circuits (maximum) 18

Color - Resin Natural (White)

Flammability 94V-0
Glow-Wire Compliant No
Guide to Mating Part No
Keying to Mating Part None
Lock to Mating Part No

Material - Metal Phosphor Bronze

Material - Plating MatingGoldMaterial - Plating TerminationGoldMaterial - ResinNylonNet Weight1.905/gNumber of Rows1

Orientation Right Angle PC Tail Length 3.35mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Tray Pitch - Mating Interface 2.54mm Pitch - Termination Interface 2.54mm Plating min - Mating 0.508µm Plating min - Termination 0.051µm Polarized to PCB Yes


Temperature Range - Operating See Product Specification

Termination Interface: Style Through Hole

**Electrical** 

Current - Maximum per Contact 2.5A
Grounding to PCB No
Voltage - Maximum 250V

**Solder Process Data** 



**China RoHS** 

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed

Low-Halogen Status
Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

**Search Parts in this Series** 

4455 Series

## **Mates With**

 $\begin{array}{l} \underline{42153} \text{ KK} \& \text{Wire-to-Board Header, } \underline{4094} \\ \text{KK} \& \text{Wire-to-Board Header, } \underline{42376} \text{ KK} \& \text{Header, } \underline{42375} \text{ KK} \& \text{Header, } \underline{42377} \text{ , } \underline{42152} \\ \text{KK} \& \text{Wire-to-Board Header, } \underline{4030} \text{ KK} \& \text{Wire-to-Board Header, } \underline{4380} \text{ KK} \& \text{Header} \end{array}$ 

Duration at Max. Process Temperature (seconds) 5

Lead-free Process Capability Wave Capable (TH only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 235

**Material Info** 

Old Part Number A-4455-AZ18A(565)

**Reference - Drawing Numbers** 

Product Specification PS-10-07 Sales Drawing SDA-4455

This document was generated on 03/27/2015

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF