

This document was generated on 12/11/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0022284251

Status: Active

Overview: KK® Interconnect System - Molex

Description: KK® 254 Breakaway Header, Vertical, 25 Circuits, Tin (Sn) Plating, Mating Pin Length

8.13mm

Documents:

<u>3D Model</u> <u>Product Specification PS-10-07 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series 42375

Application Board-to-Board, Signal, Wire-to-Board Overview KK® Interconnect System - Molex

Product Name KK® 254 UPC 800753835689

Physical

Breakaway Yes Circuits (Loaded) 25 Circuits (maximum) 25 Color - Resin Black Durability (mating cycles max) 25 First Mate / Last Break No Flammability 94V-0 **Glow-Wire Compliant** Nο Guide to Mating Part No Keying to Mating Part None Lock to Mating Part None Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination

Material - Resin High Temperature Thermoplastic


Net Weight 1.909/g Number of Rows 1

Orientation Vertical PC Tail Length 3.05mm **PCB** Locator Nο **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 2.54mm Plating min - Mating 2.540µm Plating min - Termination 2.540µm Polarized to Mating Part No Polarized to PCB No Shrouded No Stackable Nο

Temperature Range - Operating See Product Specification

Termination Interface: Style Through Hole

Surface Mount Compatible (SMC)



EU ELV

Not Relevant

EU RoHS China RoHS Compliant

REACH SVHC
No -ED/39/2015 (15
June 2015)
Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

42375 Series

Mates With

KK® Crimp Housing $\underline{2695}$, $\underline{6471}$, $\underline{7880}$, KK® PC Board Connector $\underline{4455}$

Electrical

Current - Maximum per Contact 4.0A Voltage - Maximum 250V

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

235

Material Info

Old Part Number 42375-0130

Reference - Drawing Numbers

Product Specification PS-10-07 Sales Drawing SD-42375-001

This document was generated on 12/11/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF