

This document was generated on 04/24/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 41792-0519

Status: Active

Overview: KK® Interconnect System - Molex

Description: KK® 396 Header, Right-Angle with Friction Lock, 10 Circuits, 0.38µm Gold (Au)

Selective Plating

Documents:

<u>3D Model</u> <u>Product Specification PS-08-50 (PDF)</u>
Drawing (PDF) <u>RoHS Certificate of Compliance (PDF)</u>

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series 41792

Application Power, Wire-to-Board

Overview KK® Interconnect System - Molex

Product Name KK® 396 UPC 800756032368

Physical

Breakaway No Circuits (Loaded) 10 Circuits (maximum) 10 Color - Resin Natural Durability (mating cycles max) 50 Flammability 94V-0 **Glow-Wire Compliant** No Lock to Mating Part Yes Material - Metal **Brass** Material - Plating Mating Gold Material - Plating Termination Tin Material - Resin Polyester Net Weight 4.760/q Number of Rows


Orientation Right Angle PC Tail Length 3.96mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 3.96mm Plating min - Mating 0.381µm Plating min - Termination 2.540µm Polarized to Mating Part Yes Polarized to PCB No Shrouded Partial Stackable

Temperature Range - Operating See Product Specification

Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 7.0A Voltage - Maximum 250V



EU RoHS ELV and RoHS Compliant REACH SVHC Not Reviewed Low-Halogen Status Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

41792Series

Mates With

2139 KK® Crimp Housing, 41695 KK® Crimp Housing, 6442 KK® Crimp Housing, 2145 PCB Connector, 41815 PCB Connector, 3069 KK® Crimp Housing

Solder Process Data

Duration at Max. Process Temperature (seconds) 5

Lead-free Process Capability Wave Capable (TH only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 235

Material Info

Reference - Drawing Numbers

Product Specification PS-08-50
Sales Drawing SDA-41792

This document was generated on 04/24/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF