

This document was generated on 04/23/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>22-28-1361</u>

Status: Active

Overview: KK® Interconnect System - Molex

Description: KK® 254 Breakaway Header, Right-Angle with Friction Lock, 36 Circuits, 0.38µm Gold

(Au) Selective Plating

Documents:

3D Model Product Specification PS-10-07 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980

General

Product Family PCB Headers

Series <u>42228</u>

Application Signal, Wire-to-Board

Application Tooling Part Link 11-20-1230

Overview KK® Interconnect System - Molex

Product Name KK® 254 UPC 800754256148

Physical

Breakaway Yes Circuits (Loaded) 36 Circuits (maximum) 36 Color - Resin Black Durability (mating cycles max) 100 Flammability 94V-0 **Glow-Wire Compliant** No Lock to Mating Part Yes Material - Metal **Brass** Material - Plating Mating Gold Material - Plating Termination Tin Material - Resin Nylon Net Weight 5.199/a


Number of Rows Orientation Right Angle PC Tail Length 3.05mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 2.54mm Plating min - Mating 0.381µm Plating min - Termination 2.540µm Polarized to Mating Part Yes Polarized to PCB No Shrouded Partial Stackable No

Temperature Range - Operating See Product Specification

Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 4.0A Voltage - Maximum 250V



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Low-Halogen



Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series 42228 Series

Mates With

KK® Crimp Housing $\underline{2695}$, $\underline{6471}$, $\underline{7880}$, KK® PC Board Connector $\underline{4455}$

Solder Process Data

Duration at Max. Process Temperature (seconds) 5

Lead-free Process Capability Wave Capable (TH only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 235

Material Info

Old Part Number A-42228-0071

Reference - Drawing Numbers

Product Specification PS-10-07
Sales Drawing SD-42228-001

This document was generated on 04/23/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF