

This document was generated on 02/02/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0026487121

Status: **Active**

KK® Interconnect System - Molex **Overview:**

Description: KK® 396 Breakaway Header, Vertical, 12 Circuits, Tin (Sn) Plating, Pin length

23.80mm (.937")

Documents:

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-08-50 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series 41661

Board-to-Board, Signal, Wire-to-Board Application

Application Tooling Part Link 11-20-0901

Overview KK® Interconnect System - Molex

Product Name KK® 396 **UPC** 800754906838


Physical

Yes **Breakaway** Circuits (Loaded) 12 Circuits (maximum) 12 Color - Resin Black Durability (mating cycles max) 25 First Mate / Last Break No Flammability 94V-0 **Glow-Wire Compliant** No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part None Material - Metal **Brass** Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Polyester Net Weight 4.094/g Number of Rows

Orientation Vertical PC Tail Length 4.37mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Bag Pitch - Mating Interface 3.96mm Pitch - Termination Interface 3.96mm Polarized to Mating Part No Polarized to PCB No Shrouded No Stackable Yes Surface Mount Compatible (SMC)

Temperature Range - Operating See Product Specification

Termination Interface: Style Through Hole



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant **REACH SVHC**

Not Contained Per -ED/79/2015 (17 December 2015)

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

41661 Series

Mates With

2139 KK® Crimp Housing, 41695 KK® Crimp Housing, 6442 KK® Crimp Housing, 2145 PCB Connector, 41815 PCB Connector, 3069 KK® Crimp Housing

Electrical

Current - Maximum per Contact 4.5A Voltage - Maximum 250V

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

001

Process Temperature max. C

235

Material Info

Old Part Number A-41661-A12C197

Reference - Drawing Numbers

Product Specification PS-08-50
Sales Drawing SD-41661-001

This document was generated on 02/02/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF