

This document was generated on 03/03/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0461141220

Status: Active

Overview: EXTreme LPHPower™ Connectors

**Description:** 1.27mm, 12.00mm Pitch, EXTreme LPHPower™ Receptacle Header, Vertical,

Compliant Pin, 12 Power Contacts, 20 Signal Contacts, Select Gold (Au) Plating, with

**BMI Guides** 

**Documents:** 

3D Model Application Specification AS-46114-001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Naming (1 D1)

Product Specification PS-46114-001 (PDF)

**Agency Certification** 

CSA LR19880 UL E29179

General

Product Family PCB Receptacles

Series 46114

Application Board-to-Board, Power

Application Tooling Part Link 62100-6300
Application Tooling Part Link 62201-8671
Comments Press Fit Pin

Overview <u>EXTreme LPHPower™ Connectors</u>

Product Name EXTreme LPHPower™

UPC 800756886374

**Physical** 

(p)ower-(s)ignal Configuration 12p - 20s Circuits (Loaded) 32 Circuits (maximum) 32 Color - Resin Black Durability (mating cycles max) 250 Flammability 94V-0 Glow-Wire Compliant No Guide to Mating Part Yes Keying to Mating Part None Lock to Mating Part None

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic


Net Weight 14.350/g
Number of Rows 2
Orientation Vertical
PCB Locator No
PCB Retention None
Packaging Type Tray

Pitch - Mating Interface 1.27mm, 12.00mm
Pitch - Termination Interface 1.27mm, 2.50mm
Plating min - Mating 0.762um

Plating min - Mating
Plating min - Termination
Polarized to Mating Part
Polarized to PCB
Stackable
No
Surface Mount Compatible (SMC)

0.762
Yes
Yes
Yes
Yes

Temperature Range - Operating -40°C to +105°C



**China RoHS** 

EU ELV

**Not Reviewed** 

EU RoHS

Not Reviewed REACH SVHC

Not Reviewed Halogen-Free

Status

**Not Reviewed** 

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Not Reviewed ELV Not Reviewed

Search Parts in this Series

46114 Series

**Mates With** 

45985 EXTreme LPHPower™ Header

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

**Global** 

DescriptionProduct #LPH Vertical0621006300

Receptacle Power Terminal Removal

Tool

Vertical Receptacle 0622018671

Press-In Tool

Termination Interface: Style Through Hole - Compliant Pin

**Electrical** 

Current - Maximum per Contact 30.0A Grounding to PCB No

Voltage - Maximum 250V AC (RMS)/DC

**Material Info** 

**Reference - Drawing Numbers** 

Application Specification AS-46114-001
Product Specification PS-46114-001
Sales Drawing SD-46114-120

This document was generated on 03/03/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Heavy Duty Power Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

1424439 1424438 09330062652 2-8675P1 605601-1 6340G1 6341G1 6360G1 6373G1 6374g2 6396G1 647757-1 66394-4 6643411-1 6646058-2 6646137-1 6646138-1 6646348-1 6646479-1 6646608-1 6646786-1 6646940-1 6651091-1 6651525-1 6651529-1 6651778-1 6651788-1 696465-1 696475-1 73000005059 73000005349 73000005642 73080255059 73080965046 765-15-0080A 765-16-0080B 789.700-44 789.700-54 80-1010 80-9 827381-1 829992-1 902-77-02113 PL00U-301-10D10 PM103MOOLOO PM16S1620S32-50 PM212MOOLOO PM309FOOLOO PM324FOOLCH PMHPAF11S03