

Wiha T-Handle.

The Classic for High Torques.

Hex and Nut Driver Electric.



AC 1000V
IEC 60900:2004

334N Hex Driver Electric with T-Handle.

Blade: Chrome-vanadium steel, through hardened, black-finish.
Insulation moulded directly onto blade.

Handle: Wiha T-Handle.

Standards: Manufactured acc. to EN/IEC 60900:2004. GS-Mark.

Application: For high torque transfer with minimal effort, especially for all work on or around electrical components up to 1000 V AC.

Order-No.	Hex	Length	Length	Length	Length	mm	mm	£
27928 8	4	150	176	80	26		5	4.85
27929 5	5	150	182	100	32		5	5.45
27930 1	6	150	182	100	32		5	6.15
27931 8	8	150	182	100	32		5	7.05



AC 1000V
IEC 60900:2004

336N Hex Driver Electric with T-Handle.

Blade: Chrome-vanadium steel, through hardened, nickel-plated.
Insulation moulded directly onto blade.

Handle: Wiha T-Handle.

Standards: Similar to DIN 7440. Manufactured acc. to EN/IEC 60900:2004. GS-Mark.

Application: For high torque transfer with minimal effort, especially for all work on or around electrical components up to 1000 V AC.

Extra: Recess in shank to accommodate for long screws.

Order-No.	Hex	Length	Length	Length	Length	mm	mm	£
27932 5	8	200	232	100	32		5	14.05
27933 2	10	230	262	100	32		5	15.30
27934 9	13	230	262	100	32		5	16.65
27935 6	17	230	268	120	38		5	18.25

Hex and Nut Driver. Inch Sizes.



334 Zoll Hex Driver with T-Handle.

Inch Sizes.

Blade: Chrome-vanadium steel, through hardened, nickel-plated.

Handle: Wiha T-Handle.

Application: For high torque transfer with minimal effort.

Order-No.	Hex	Length	Length	Length	Length	mm	mm	£
02802 2	3/32	150	182	80	26	2.38	10	2.58
02803 9	7/64	150	182	80	26	2.78	10	2.58
02804 6	1/8	150	182	80	26	3.18	10	2.50
02805 3	9/64	150	182	80	26	3.57	10	2.50
02806 0	5/32	150	182	80	26	3.97	10	2.35
02807 7	3/16	150	182	100	32	4.76	10	2.66
02808 4	7/32	150	182	100	32	5.56	10	3.05
02809 1	1/4	150	182	100	32	6.35	10	3.20
02810 7	5/16	150	182	100	32	7.94	10	3.47
02811 4	3/8	150	188	120	38	9.53	10	6.10



336 Zoll Hex Nut Driver with T-Handle.

Inch Sizes.

Blade: Chrome-vanadium steel, through hardened, nickel-plated.

Handle: Wiha T-Handle.

Application: For high torque transfer with minimal effort.

Extra: Recess in shank to accommodate for long screws.

Order-No.	Hex	Length	Length	Length	Length	mm	mm	£
02819 0	3/16	150	182	100	32	4.76	10	5.10
02820 6	1/4	150	182	100	32	6.35	10	5.50
02821 3	5/16	150	182	100	32	7.94	10	5.90
02822 0	3/8	150	182	100	32	9.53	10	6.30
02823 7	7/16	150	182	100	32	11.11	10	7.70
02824 4	1/2	150	182	100	32	12.70	10	8.40

Wiha Info

Colour-coding system:

- red:
metric hex blades
- yellow:
inch hex blades
- green:
TORX® blades
- light green:
TORX PLUS® blades

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Screwdrivers, Nut Drivers & Socket Drivers](#) category:

Click to view products by [Wiha](#) manufacturer:

Other Similar products are found below :

[1406504-2](#) [2-21006-8](#) [27850](#) [CE-16-03400-00-HNDLE-TORQ](#) [30246](#) [323451-000](#) [46722](#) [16538](#) [XW4Z-00B](#) [96025](#) [96030](#) [96560](#) [96703](#)
[96430](#) [31830](#) [92270](#) [96012](#) [96436](#) [96536](#) [92064](#) [92008](#) [72820](#) [92005](#) [76070](#) [96520](#) [92040](#) [36372](#) [96416](#) [92024](#) [96420](#) [76005](#) [96570](#)
[72823](#) [96325](#) [96525](#) [96720](#) [31832](#) [76019](#) [92004](#) [76007](#) [92069](#) [92020](#) [76021](#) [96523](#) [96510](#) [96427](#) [96425](#) [96415](#) [96320](#) [92073](#)