

KX022 Accelerometer

2x2x0.9mm Accelerometer with FIFO/FILO Buffer



FEATURES

- 2x2x0.9mm LGA package
- Full-featured algorithm engine including:
 - Tap detection, orientation detection, activity monitoring, and embedded motion wake-up algorithms
- Low current consumption in all modes:
 - 0.9 μ A in standby,
 - 10 μ A at normal resolution, and
 - 145 μ A at high resolution
- Two interrupt registers
- User-configurable, embedded wake-up function to conserve battery power
- Internal voltage regulator to maintain constant internal operating voltages throughout the 1.8 - 3.6V input supply range

APPLICATIONS

- User Interface
- Power Management
- Active/Inactive Monitoring
- Device Orientation
- Inclination and Tilt Sensing
- Gesture Recognition
- Pedometer/Activity Monitoring
- Motion-controlled user interface


FOR

- Smartphones and Mobile Devices
- Laptops
- Gaming and Virtual Reality
- Health and Fitness

PRODUCT OVERVIEW

The KX022 is a robust, low-power, I2C/SPI, 3-axis accelerometer with integrated FIFO/FILO buffer that features a wide range of embedded functionality, including tap detection, orientation, activity, and wake-up algorithms.

Kionix's XAC sensor provides outstanding stability with a market-leading combination of improved shock, reflow, and thermal performance. The KX022 also offers accelerometer outputs with 16-bit resolution for greater precision. User-selectable parameters include $\pm 2g$, 4g or 8g ranges and Output Data Rates (ODR) with programmable high-pass and low-pass filters. It is packaged in an ultra-small, 12-pin, 2x2x0.9mm LGA plastic package.



KX022 Accelerometer

2x2x0.9mm Accelerometer with FIFO/FILO Buffer



The performance parameters below are programmed and tested at 2.6 volts and T = 25°C. The device can accept supply voltages from 1.8V to 3.6V. Due to internal voltage regulators, there should be minimal change with supply voltage variations.

PERFORMANCE SPECIFICATIONS			
PARAMETERS	UNITS	KX022-1020	CONDITION
Range	g	±2.0, ±4.0, ±8.0	User-selectable full-scale output range
Sensitivity ¹	counts/g	16384, 8192, 4096	16-bit
		64, 32, 16	8-bit
0g Offset vs. Temp	mg/°C	0.2	-40°C to +85°C
Sensitivity vs. Temp	%/°C	0.01	-40°C to +85°C
Mechanical Resonance ²	Hz	3500 (xy) 1800 (z) typical	-3dB
Output Data Rate (ODR) ³	Hz	0.781 min; 50 typical; 1600 max	
Non-Linearity	% of FS	0.6 typical	% of full scale output
Cross-axis Sensitivity	%	2.0 typical	
Noise ⁴	mg	0.75 typical	
I ² C Communication Rate	MHz	3.4 max	
SPI Communication Rate	MHz	10 max	
Power Supply	V	1.8V – 3.6V typical	
Current Consumption ⁵	µA	145 typical	High resolution (RES = 1)
		10 typical	Low resolution (RES = 0)
		0.9 typical	Standby
ENVIRONMENTAL SPECIFICATIONS			
PARAMETERS	UNITS	KX022-1020	CONDITION
Operating Temperature	°C	-40 to 85	Powered
Storage Temperature	°C	-55 to 150	Un-powered
Mechanical Shock	g	5,000, 0.5 ms 10,000, 0.2 ms	Powered or un-powered, halversine
ESD	V	2,000	Human body model

NOTES

- ¹ Resolution and acceleration ranges are user selectable via I²C or SPI.
- ² Resonance as defined by the dampened mechanical sensor.
- ³ User selectable through I²C or SPI.
- ⁴ RMS at 50Hz with low-pass filter = ODR/9.
- ⁵ Current varies with Output Data Rate (ODR).

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [kionix](#) manufacturer:

Other Similar products are found below :

[EVAL-KXTI9-1001](#) [EVAL-KXTIA-1006](#) [EVAL-KXCJ9-1008](#) [EVAL-KXTC9-2050](#) [EVAL-KX023-1025](#) [KMX62-1031-EVB0B0](#) [KX224-1053-SR](#) [KX224-I2C-EVK-001](#) [EVAL-KX022-1020](#) [KX112-1042-EVB0A0](#) [KX126-1063-EVB0A1](#) [KX224-1053-EVB0B0](#) [KX124-1051-EVB0B0](#) [KX122-1037-EVB0A0](#) [KXTIA-1006](#) [KX132-1211-EVK-001](#) [KX222-1054-SR](#) [KXCJ9-1008-PR](#) [KXCNL-1010-FR](#) [KXCJ9-1008-FR](#) [KXTH9-2083-FR](#) [KMX63-1055](#) [KXR94-2283-FR](#) [KX126-1063](#) [KX022-1020-PR](#) [BM2P189TF-E2](#) [KXTF9-2050-FR](#) [KXTIK-1004-FR](#) [KX122-1037](#) [KX222-1054](#) [KX132-1211](#) [KXTJ3-1057](#) [KX134-1211](#)