

This document was generated on 02/22/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0683011015
Status: Obsolete

Overview: kk

Description: 2.54mm (.100") Pitch KK® Header, Surface Mount, Single Row, Vertical, without

Shroud, 4 Circuits, with 6.10mm (.240") Mating Pin Length

Documents:

Drawing (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>68301</u>

Application Board-to-Board, Signal, Wire-to-Board

Physical

Breakaway Yes Circuits (Loaded) 4 Circuits (maximum) 4 Color - Resin Black Durability (mating cycles max) 25 First Mate / Last Break No Flammability 94V-0 **Glow-Wire Compliant** No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part None

Material - Metal Phosphor Bronze

Material - Plating Mating Tin Material - Plating Termination Tin Material - Resin Nylon Number of Rows 1 Orientation Vertical **PCB** Locator No **PCB** Retention None Packaging Type Tray

Pitch - Mating Interface2.54mm (.100")Pitch - Termination Interface2.54mm (.100")Plating min - Mating2.540μm (100μ")Plating min - Termination2.540μm (100μ")

Polarized to Mating Part No Shrouded No Stackable No


Temperature Range - Operating -55°C to +105°C Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 3A Voltage - Maximum 250V

Solder Process Data

Lead-free Process Capability Reflow Capable (SMT only)



EU RoHS ELV and RoHS Compliant REACH SVHC Not Reviewed Low-Halogen Status Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

68301Series

Mates With

KK® Crimp Terminal Housing <u>2695</u>, <u>6471</u>, <u>7880</u>. KK® PC Board Connector <u>4455</u>, <u>42625</u>. <u>7720</u> KK® IDT Double Cantilever Contact, <u>70430</u> C-Grid SLTM Single Row. <u>70107</u> SLTM Wire-to-Wire Crimp Housing. <u>7859</u> C-Grid® Shu

Process Temperature max. C 235

Material Info

Reference - Drawing Numbers

Product Specification PS-87920-019
Sales Drawing SD-68301-001

This document was generated on 02/22/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF