

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [70929-2009](#)  
**Status:** **Active**  
**Overview:** [LFH™ Interconnect System](#)  
**Description:** 1.27mm Pitch LFH™ Matrix 50 Plug Cable Kit, Subassembly, 60 Circuits, Bright Nickel (Ni) Front Shell Plating

**Documents:**

<a href="#">3D Model</a>	<a href="#">Application Specification AS-70929-001 (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Application Specification AS-71624-001 (PDF)</a>
<a href="#">Product Specification PS-70928 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>

**Agency Certification**

CSA	LR19980
UL	E29179

**General**

Product Family	I/O Connectors
Series	<a href="#">70929</a>
Application	Wire-to-Board
Comments	I/O Plug Connector Subassembly Use Tool 62200-1500 for inserting sticks into subassembly 70984 Terminal Sticks Supplied Separately
Component Type	I/O Plug Connector Subassembly
Overview	<a href="#">LFH™ Interconnect System</a>
Product Name	LFH™
Type	N/A
UPC	822350303040

**Physical**

Boot Color	N/A
Circuits (Loaded)	60
Circuits (maximum)	60
Color - Resin	Black
Durability (mating cycles max)	500
Flammability	94V-0
Gender	Plug
Lock to Mating Part	None
Material - Metal	Aluminum
Material - Plating Mating	N/A
Material - Resin	High Temperature Thermoplastic
Net Weight	4.846/g
Number of Rows	4
Orientation	Vertical
PCB Retention	N/A
Packaging Type	Tray
Panel Mount	Yes
Pitch - Mating Interface	1.27mm
Pitch - Termination Interface	1.27mm
Polarized to Mating Part	Yes
Polarized to PCB	N/A
Ports	1
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-20°C to +80°C
Termination Interface: Style	N/A
Waterproof / Dustproof	No



**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC Contains SVHC: No**  
**Low-Halogen Status Low-Halogen**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[70929Series](#)

**Mates With**

[70928 LFH™ Receptacle](#)

**Use With**

[70984 Terminal Stick](#), [71245 ClampShell](#), [71628 Guide Pin](#), [Guide Sleeve 71629](#) or [71771](#), [70982 Hex Screw Kit](#)

**Electrical**

Current - Maximum per Contact	1.0A
Shield Type	Full Shield
Shielded	Yes
Voltage - Maximum	40V AC (RMS)

**Material Info****Reference - Drawing Numbers**

Application Specification	AS-70929-001, AS-71624-001
Product Specification	PS-70928, RPS-70928-002
Sales Drawing	SDA-70929-20**

This document was generated on 05/21/2015

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Molex](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [67230-005LF](#)