

This document was generated on 02/20/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	75783-0043		
Status:	Active		
)verview:	iPass [™] Connector S	System	
Description: iPass™ I/O Surface M			
		Mount Receptacle, Right Angle, Internal Assembly with Shell, 26	
	Circuit, 0.76µm Goid	d (Au), Through Hole Option, Tail Length 2.79mm, Dual Key	
Documents:			
3D Model		Product Specification PS-75783-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	E STATE
			Se Se
Agency Certificat	ion		image - Reference only
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
Comorol			ELV and RoHS
General			Compliant
Product Family		I/O Connectors	REACH SVHC
Series		<u>75783</u>	Not Reviewed
Application		Wire-to-Board	Low-Halogen Status
Comments		Positive or passive latching cable available	Low-Halogen
Component Type		Receptacle	
Electrical Model		Yes	Need more information on product
Overview		iPass™ Connector System	environmental compliance?
Product Name		iPass™, Mini Multi-Lane, PCI Express*	Email productcompliance@molex.com
		N/A	
Type		822350092272	For a multiple part number RoHS Certifica
UPC		822350092272	Compliance, <u>click here</u>
Physical			Please visit the <u>Contact Us</u> section for any
Circuits (Loaded)		26	non-product compliance questions.
Circuits (maximum)		26	
Color - Resin		Black	
Durability (mating cycles max)		250	
Flammability		94V-0	Search Parts in this Series
Gender		Female	75783Series
Keying to Mating Part		Yes	
Lock to Mating Part		None	
Material - Metal		Copper-Nickel-Zinc, High Performance Alloy (HPA)	Use With
	na		iPass™ Cable Assemblies, <u>79575</u> , <u>795</u>
Material - Plating Mati		Gold	, <u>74562</u> , <u>74563</u> , <u>79536</u> , <u>74573</u> , <u>74569</u>
Material - Plating Termination		Tin Llick Tarana antona Tharman Iantia	74586
Material - Resin		High Temperature Thermoplastic	,
Net Weight		2.595/g	
Number of Rows		2	
Orientation		Right Angle	
PC Tail Length		2.79mm	
PCB Locator		Yes	
PCB Retention		Yes	
PCB Thickness - Recommended		2.36mm	
Packaging Type		Embossed Tape on Reel	
Panel Mount		No	
Pitch - Mating Interface		0.80mm	
Pitch - Mating Interface		0.80mm	
Plating min - Mating		0.762µm	
Plating min - Termination		2.540µm	
Polarized to Mating Part		Yes	
Ports		1	
Surface Mount Compatible (SMC)		Yes	
Temperature Range - Operating		-40°C to +80°C	

Termination Interface: Style Waterproof / Dustproof Wire Insulation Diameter Wire Size AWG	Surface Mount, Through Hole No N/A N/A
Electrical Current - Maximum per Contact Grounding to Panel Voltage - Maximum	0.5A None 30V AC (RMS)/DC
Solder Process Data Duration at Max. Process Temperature (seconds) Lead-free Process Capability Max. Cycles at Max. Process Temperature Process Temperature max. C	20 Reflow Capable (SMT only) 1 260
Material Info	
Reference - Drawing Numbers Electrical Model Document Product Specification S-Parameter Model Sales Drawing	EE-75586-001 PS-75783-001 SP-75586-001 SD-75783-001

This document was generated on 02/20/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 RJE231881317T
 MP1010RX-1000
 MP44RX-1000
 GAX-3-66
 GAX-8-62
 93606-0253
 GD-A-44
 GDCX-PA-66-50
 GDCX-PN-64
 GDCX-PN-64

 PN-66
 GDCX-PN-66-50
 GDLX-A-66
 GDLX-A-88
 GDLX-N-66
 GDLX-S-88K
 GDTX-S-88-50
 GDX-PA-1010
 GLX-N-1010M-BLK

 GLX-N-44M
 GLX-S-88M-BLK
 GMX-N-1010
 GMX-S-1010
 GMX-S-66
 GMX-SMT2-N-1010
 GMX-SMT2-N-64-50
 GMX-SMT2-S6-88

 GMX-SMT4-N-88
 GPX-2-64
 GRT1-BT1-5
 GSGX-N-2-88
 GSX-NS2-88-3.05
 GSX-NS2-88-3.05-50
 GSX-NS-88-3.05-30
 GSX-NS-88-3.05-30

 3.05-50
 GSX-NS-88-3.68
 1-1775629-2
 GWLX-S-88-GR
 GWLX-S9-88-YG
 1300500326
 1300500227
 1300530003
 1300570002
 1324640-4

 RJ11FTVC2G
 RJ11FTVC2N
 RJFTVX2SA1G
 132764-001
 1400000
 1413176
 1413235