

This document was generated on 02/12/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: **75783-0252**

Status: Active

Overview: iPass™ Connector System

Description: iPass™ I/O Surface Mount Receptacle, Right Angle, Internal Assembly with Shell, 50

Circuit, 0.76µm Gold (Au), Through Hole Option, Tail Length 3.18mm, Universal Key

Documents:

3D Model Application Specification AS-75783-001 (PDF)

<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Product Specification PS-75783-001 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series 75783
Application Wire-to-Board

Comments Positive or passive latching cable available

Component Type Receptacle

Electrical Model Yes

Overview <u>iPass™ Connector System</u>

Product Name iPass™, Mini Multi-Lane, PCI Express*

Type N/A

UPC 800756839769

Physical

Circuits (Loaded) 50
Circuits (maximum) 50
Color - Resin Black
Durability (mating cycles max) 250
Flammability 94V-0
Gender Female

Keying to Mating Part Yes
Lock to Mating Part None

Material - Metal Copper-Nickel-Zinc, High Performance Alloy (HPA)

Material - Plating Mating Gold Material - Plating Termination Tin


Material - Resin High Temperature Thermoplastic

Net Weight 3.863/g Number of Rows 2

Orientation Right Angle
PC Tail Length 3.18mm
PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 2.79mm

Packaging Type Embossed Tape on Reel

Panel Mount
Pitch - Mating Interface
Pitch - Termination Interface
Plating min - Mating
Plating min - Termination
Polarized to Mating Part
Ports
1
Surface Mount Compatible (SMC)
Pitch - No
0.80mm
0.762
0.80mm
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0.762
0



China RoHS

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed

Low-Halogen Status
Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

<u>75783</u>Series

Use With

iPass[™] Cable Assemblies, $\underline{79575}$, $\underline{79576}$, $\underline{74562}$, $\underline{74563}$, $\underline{79536}$, $\underline{74573}$, $\underline{74569}$, $\underline{74586}$

Temperature Range - Operating -40°C to +80°C

Termination Interface: Style Surface Mount, Through Hole

Waterproof / Dustproof No
Wire Insulation Diameter N/A
Wire Size AWG N/A

Electrical

Current - Maximum per Contact 0.5A
Grounding to Panel None

Voltage - Maximum 30V AC (RMS)/DC

Solder Process Data

Duration at Max. Process Temperature (seconds) 20

Lead-free Process Capability Reflow Capable (SMT only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 260

Material Info

Reference - Drawing Numbers

Application Specification AS-75783-001
Electrical Model Document EE-75586-001
Product Specification PS-75783-001
S-Parameter Model SP-75586-001
Sales Drawing SD-75783-001

This document was generated on 02/12/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Telecom ICs category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

87180-066 B78476A9558A003 4C9965 RH1041W-MFP-GNL 5C3263 7J8004 SCMS7D43AY100PT1 43841-0003-CUT-TAPE

HX6106NLT 75586-0004-CUT-TAPE JC0-0201NL 0432498916 0757840156 93899-001LF 9455511103 10118067-5136210LF 69253-001

H1062 P129 T7015NLT T1231NL 432238149 428786360 432498908 441500007 446200003 432028918 432498925 428788458

443800019 443801016 754500001 757830252 757840212 757865001 950432801 760925002 133148 ST7010QNL T-1250SCT T3023NL

66010-004LF 203156 68899-002LF 73327-111LF 95672-001LF 95678-001ALF 45-5614-BU DS2174QN+ CPC1465D