

This document was generated on 06/26/2015

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0757865001

Status: Active

Overview: SFP+ and SFP Interconnect Solutions

**Description:** Small Form-factor Pluggable (SFP) Stacked 2-by-1 Multi-Port Connector with 4

Lightpipes, with Press-fit PC Tails, 40 Circuits, Square Cut Gasket, Lead-Free

**Documents:** 

<u>Application Specification AS-76090-001 (PDF)</u>
<u>Drawing (PDF)</u>

<u>Packaging Specification PK-75310-001 (PDF)</u>

Product Specification PS-75310-001 (PDF)

RoHS Certificate of Compliance (PDF)

Application Specification AS-75310-001 (PDF)

**Agency Certification** 

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>75786</u>

Application Module-to-Board

Comments With 4 Lightpipes|Square Cut Gasket

Component Type Receptacle

Overview SFP+ and SFP Interconnect Solutions

Product Name SFP Type N/A

UPC 822350236348

**Physical** 

Circuits (Loaded) 40
Circuits (maximum) 40
Color - Resin Black
Durability (mating cycles max) 200
Flammability 94V-0
Lock to Mating Part Yes

Material - Metal High Performance Alloy (HPA)

Material - Plating Mating Gold
Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 32.942/g
Orientation Right Angle
PC Tail Length 3.05mm
PCB Locator Yes
PCB Retention Yes
PCB Thickness - Recommended 2.40mm
Packaging Type Tray


Packaging Type Panel Mount No Pitch - Mating Interface 0.80mm Pitch - Termination Interface 0.80mm Plating min - Mating 0.762µm Plating min - Termination 0.762µm Polarized to Mating Part Yes Polarized to PCB Yes Surface Mount Compatible (SMC) Nο

Temperature Range - Operating -40°C to +85°C

Termination Interface: Style Through Hole - Compliant Pin

No

Waterproof / Dustproof



EU ELV

**Not Relevant** 

EU RoHS China RoHS

**Compliant**REACH SVHC

Contains SVHC(2014 December 17): No Halogen-Free

**Status** 

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

**Search Parts in this Series** 

75786 Series

**Use With** 

75951-0999 SFP Dust Plug

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

**Description** Product #
Stacked Multi-Port 0622029960

Extraction Tool, 2 by

1 Tall

Stacked Multi-Port 0622030145

Insertion Tool, 2 by 1

all

**Electrical** 

Current - Maximum per Contact 0.5A

Shield Type EMI Gasket

Shielded Yes Voltage - Maximum 30V

**Solder Process Data** 

Lead-freeProcess Capability N/A

**Material Info** 

**Reference - Drawing Numbers** 

Application Specification AS-75310-001, AS-76090-001

Packaging Specification PK-75310-001
Product Specification PS-75310-001
Sales Drawing SD-75786-001

This document was generated on 06/26/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Telecom ICs category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

87180-066 B78476A9558A003 4C9965 RH1041W-MFP-GNL 5C3263 7J8004 SCMS7D43AY100PT1 43841-0003-CUT-TAPE

HX6106NLT 75586-0004-CUT-TAPE JC0-0201NL 0432498916 0757840156 93899-001LF 9455511103 10118067-5136210LF 69253-001

H1062 P129 T7015NLT T1231NL 432238149 428786360 432498908 441500007 446200003 432028918 432498925 428788458

443800019 443801016 754500001 757830252 757840212 757865001 950432801 760925002 133148 ST7010QNL T-1250SCT T3023NL

66010-004LF 203156 68899-002LF 73327-111LF 95672-001LF 95678-001ALF 45-5614-BU DS2174QN+ CPC1465D