

This document was generated on 09/05/2013

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 85003-2529

Status: **Active** DIN 41612 **Overview:** 

2.54mm Pitch DIN 41612 Header, Style C, Right Angle , Through Hole ,1µm Selective **Description:** 

Gold (Au), 96 Circuits, First-Mate-Last-Break Pins Available, Lead-Free

**Documents:** 

RoHS Certificate of Compliance (PDF) 3D Model

**Drawing (PDF)** 

**Agency Certification** 

**CSA** LR19980 UL E29179

General

**Product Family Backplane Connectors** 

85003 Series Application Daughtercard Component Type PCB Header Overview DIN 41612

**Product Name** IEC 603-2/DIN 41612

Style С

**UPC** 822348083374

**Physical** 

Circuits (Loaded) 96 Circuits (maximum) 96 Durability (mating cycles max) 500 First Mate / Last Break Yes Flammability 94V-0 Guide to Mating Part No Keying to Mating Part Yes Material - Plating Mating Gold Net Weight 13.628/q Number of Columns 16

**Number of Pairs** Open Pin Field

Number of Rows

Orientation Right Angle PC Tail Length 3.00mm **PCB** Locator No **PCB** Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Tray Pitch - Mating Interface 2.54mm Pitch - Termination Interface 2.54mm Polarized to PCB Yes Stackable No Surface Mount Compatible (SMC) No


Temperature Range - Operating -55°C to +125°C Termination Interface: Style Through Hole

**Electrical** 

Current - Maximum per Contact 1A

Data Rate 622.0 Mbps Voltage - Maximum 250V AC (RMS)

**Solder Process Data** 



**EU RoHS ELV and RoHS** Compliant **REACH SVHC** Not Reviewed

**Low-Halogen Status Not Reviewed** 

## **China RoHS**

Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

85003Series

**Mates With** 

85042, 85052 Backplane Header

Duration at Max. Process Temperature (seconds) 10

Lead-free Process Capability Wave Capable (TH only)

Process Temperature max. C 260

**Material Info** 

**Reference - Drawing Numbers** 

Sales Drawing SD-85003-2529

This document was generated on 09/05/2013

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

09231126901 PCN10F-24P-2.54DS(72) 004.767 02221602702 024069 602427301412000 013275 691327-1 74670-0732 74680-0340
75880-0015 76453-0014 86093159ALF 923454 QLC260R 120X10099X 120X10019X 120X10089X 120X10129X 121A10039X
121A10309X 122A10019X 122A10029X 122A10249X 122A10669X 122A11089X 122A13089X 121B10409X 122A10089X
122A10129X 122A10349X 122A13359X 1377391-4 DIN-048CPC-SR1-MH 1393583-2 1393726-7 140X10059X 140X10129X 143-1913000 143-1908-000 1484472-1 173052 2110070-1 2110070-2 CBC20T00-008FDS5-0-1-002VR 983-0SE12-12P6 17041102202 1726995036 173051 20 8457096 010 025