Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



9438 Hook-up/Lead - Direct Burial Cable

For more Information please call

1-800-Belden1



General Description:

Tinned copper conductor. Black high-density polyethylene insulation.

Physical Characteristics (Overall)

AWG:

Conductors AWG Stranding 14 104x34

Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
HDPE - High Density Polyethylene	0.8128

Overall Insulation

Overall Cable

Overall Nominal Diameter: 3.531 mm

Mechanical Characteristics (Overall)

Non-UL Temperature Rating: Bulk Cable Weight: 32.740 Kg/Km

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

	EU Directive 2011/65/EU (ROHS II):	Yes
	EU CE Mark:	No
	EU Directive 2000/53/EC (ELV):	Yes
	EU Directive 2002/95/EC (RoHS):	Yes
	EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2004
	EU Directive 2002/96/EC (WEEE):	Yes
	EU Directive 2003/11/EC (BFR):	Yes
	CA Prop 65 (CJ for Wire & Cable):	Yes
	MII Order #39 (China RoHS):	Yes
Plenum/Non-Plenum		
	Plenum (Y/N):	No

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km) 8.26812

600 V RMS Suggested Working Voltage:

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9438 0101000	1,000 FT	20.000 LB	BLACK	С	14 STR PE BLK

Notes: C = CRATE REEL PUT-UP.

Page 1 of 2 11-05-2015

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



9438 Hook-up/Lead - Direct Burial Cable

Revision Number: 1 Revision Date: 06-23-2010

© 2015 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2 11-05-2015

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 8538-009-1000 ATFC0311-20-5D EF5675-000
BFWUL3239-24-PINK 22759/34-16-9CS2621 22759/42-24-9CS2620 933205-000 284711-000 961473-000 30802-009-250 30808-010-500
30810-010-500 99M0111-20-2 A00594-000 190571-000 22759/41-12-9CS2620 22759/41-16-9CS2620 22759/43-10-9CS2873 265925-000
CM9524-000 CMC-0553-1-9 31510-010-250 31514-009-500 32412-009-500 34401-010-250 34402-010-500 M81044/9-4-9 391441-BK007
400R0111-10-9 431660-000 ATFC0311-20-0 ATFC0311-20-3 44/7024-26-9-9 44A0112-22-9CS3184 456157-000 BFW-UL3239-24WHITE 55/0312-26-6L-CS2570 55A0811-12-9 55A6087-20-9-9-9 55A6315-22-9-9CS2632 55A7400-22-9/96-9CS2275 55A9002-30-5
55PC0211-20-5CS2502 55PC0811-6-9CS2637 55PC1211-22-9-9CS3278