

This document was generated on 09/30/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0746971001

Status: **Active**

VHDM-HSD™ Backplane Connectors **Overview:**

VHDM-HSD™ Backplane Header, 2.00mm Pitch, 5-Row, Guide Pin Signal Module, **Description:**

> Shield End Version, 40 Circuits, Pin Length 4.75mm. Series:74702 Enables designers to create custom loaded connectors utilizing standard pin lengths 4.25, 4.75, 5.15 and

6.25mm

Documents:

3D Model Packaging Specification PK-74696-003 (PDF) Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-74031-999 (PDF)

Agency Certification

CSA LR19980

General

Product Family Backplane Connectors

Series 74697 Application Backplane **Application Tooling Documents** TM-622010999 No Keying Position Comments Component Type **PCB** Header

Overview VHDM-HSD™ Backplane Connectors

Product Name VHDM-HSD™ **UPC** 800756544656

Physical

Number of Rows

40 Circuits (Loaded) Circuits (maximum) 40 Color - Resin Black Durability (mating cycles max) 200 First Mate / Last Break No Flammability 94V-0 Guide to Mating Part Yes Keying to Mating Part None

Material - Metal High Performance Alloy (HPA), Stainless Steel

5

Material - Plating Mating Gold Material - Plating Termination Matte Tin

Material - Resin High Temperature Thermoplastic


Net Weight 7.694/aNumber of Columns

Number of Pairs Open Pin Field

Orientation Vertical PC Tail Length 2.50mm **PCB** Locator No **PCB** Retention None PCB Thickness - Recommended 1.80mm Packaging Type Tube Pitch - Mating Interface 2.00mm Plating min - Mating 0.762um Plating min - Termination 0.762µm Polarized to PCB Yes Stackable Yes

Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -55°C to +105°C



EU ELV Not Relevant

EU RoHS China RoHS

Not Compliant REACH SVHC Not Contained Per -ED/21/2016 (20 June

2016)

Halogen-Free Status Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS 50 Image **ELV** Not Relevant

Search Parts in this Series

74697 Series

Mates With

74670 VHDM-HSD™ Daughtercard

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # Signal Header, 5-0622020201 Row by 10-Wide,

20.00mm

Signal Pin Inserter

0622015700

Repair Tool

5-Row Pin and 0622015810

Shield Repair Tool

Termination Interface: Style Through Hole - Compliant Pin 5-Row Shield 0622016010 Extraction Tool

Electrical

Current - Maximum per Contact 1.0A
Data Rate 5.0 Gbps

Real Signals (per 25mm) 48

Voltage - Maximum 120V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Packaging Specification PK-74696-003
Product Specification PS-74031-999
Sales Drawing SD-74697-002

Note: HDM, HDM+, VHDM, VHDM-HSD and GbX are trademarks or registered trademarks of Amphenol TCS.

This document was generated on 09/30/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

09231126901 PCN10F-24P-2.54DS(72) 004.767 02221602702 024069 602427301412000 013275 691327-1 74670-0732 74680-0340
75880-0015 76453-0014 86093159ALF 923454 QLC260R 120X10099X 120X10019X 120X10089X 120X10129X 121A10039X
121A10309X 122A10019X 122A10029X 122A10249X 122A10669X 122A11089X 122A13089X 121B10409X 122A10089X
122A10129X 122A10349X 122A13359X 1377391-4 DIN-048CPC-SR1-MH 1393583-2 1393726-7 140X10059X 140X10129X 143-1913000 143-1908-000 1484472-1 173052 2110070-1 2110070-2 CBC20T00-008FDS5-0-1-002VR 983-0SE12-12P6 17041102202 1726995036 173051 20 8457096 010 025