

This document was generated on 02/04/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0709282007

Status: Active

Overview: LFH™ Interconnect System

Description: 1.27mm Pitch LFH™ Matrix 50 Receptacle, Shielded, Right Angle, 3.18mm PC Tail

Length, Screw Hole M3 Thread, Gold Plating, 60 Circuits

Documents:

3D Model Test Summary TS-70928-001 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-70928 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family I/O Connectors

Series <u>70928</u>

Application Board-to-Board, Wire-to-Board

Comments Dim.B for 1.00mm max. Panel Thickness is 9.65mm and

10.67mm for 1.63mm max. Panel Thickness

Component Type Receptacle

Overview <u>LFH™ Interconnect System</u>

Product Name LFH $^{\text{TM}}$ Type N/A

UPC 800754810982

Physical

Circuits (Loaded) 60
Circuits (maximum) 60
Color - Resin Black
Durability (mating cycles max) 500
Flammability 94V-0
Gender Receptacle

Keying to Mating Part

Lock to Mating Part

Yes

Material - Metal Beryllium Copper

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic


Net Weight 7.038/g Number of Rows 4

Orientation Right Angle
PC Tail Length 3.18mm
PCB Retention None

PCB Thickness - Recommended 2.40mm Packaging Type Tube **Panel Mount** Yes Pitch - Mating Interface 1.27mm Pitch - Termination Interface 1.27mm Plating min - Mating 0.762µm Plating min - Termination 2.540um Polarized to Mating Part Yes Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -20°C to +80°C Termination Interface: Style Surface Mount

Wire Size AWG N/A



EU ELV Not Relevant

NOT Relevant

EU RoHS China RoHS

Compliant REACH SVHC Not Contained Per

-ED/79/2015 (17 December 2015)

Halogen-Free Status

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

70928 Series

Mates With
70929 LFH™ Plug

Use With

 $\underline{71628}$ Guide Pin, Guide Sleeve 71629 or

71771, <u>70982</u> Hex Screw Kit

Electrical

Current - Maximum per Contact 1.0A Shielded Yes Voltage - Maximum 40V

Solder Process Data

Duration at Max. Process Temperature (seconds) 040

Lead-freeProcess Capability SMC&WAVE

Max. Cycles at Max. Process Temperature 003
Process Temperature max. C 245

Material Info

Reference - Drawing Numbers

Product Specification PS-70928, RPS-70928-001, RPS-70928-002

Sales Drawing SDA-70928-20** Test Summary TS-70928-001

This document was generated on 02/04/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Micro-D Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

M243082311F M2430834F M24308/4-6F 65-1920-15 M83513/01-HN M83513/03-A10N M83513/03-B14C M83513/03-D09C M83513/03-D11N M83513/03-G02N M83513/03-G05N M83513/03-G08C M83513/03-G09N M83513/03-G12N M83513/03-H13N M83513/04-E15N M83513/04-G04C M83513/10-E01NP M83513/13-B01NP M83513/13-C01NN M83513/16-A01CP M83513/22-D01NP M83513/25-B01NP 6R2004A30F015 6R4006A28A120 703006A13F060 704002A03F200 705001A13F120 7-1532020-5 748567-1-P MDB1-31SH003 MDM-15PBS-L58 MDM-15PCBRM7T MDM-15PH003B-A174 75-068624-59S MDM-15PH034B MDM-15SH001L MDM-15SH004B MDM-21PH003K MDM-25PH003B-A174 MDM-25PHW01F-A174 MDM-37PH006L-A174 MDM-37PH048M5-A174 MDM-37SCBRP-A174 MDM-51PBS-L56 MDM-51PSF MDM-51SH003M7 MDM-51SSM7-A174 MDM-9PBSP-L58 MDM-9PH003M7