

This document was generated on 05/14/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	79107-7074 Active <u>Milli-Grid™ Connector System</u> 2.00mm Pitch Milli-Grid™ Receptacle, Vertical, Through Hole, Dual Row, 3.00mm Tail Length, 0.76µm Gold (Au) Selective Plating, 50 Circuits, Lead-Free		2 2 2 2 2
Overview: Description:			
Documents: <u>3D Model</u> Drawing (PDF)		Product Specification PS-79107 (PDF) RoHS Certificate of Compliance (PDF)	Seri
General			image - Reference only
Product Family		PCB Receptacles	
Series		<u>79107</u>	EU RoHS China RoHS
Application		Board-to-Board, Signal	ELV and RoHS
Overview		Milli-Grid [™] Connector System	Compliant
Product Name		Milli-Grid™	REACH SVHC
UPC		822348474936	Contains SVHC: No
Physical			Low-Halogen Status
Circuits (Loaded)		50	
Circuits (maximum)		50	Need more information on product environmental compliance?
Color - Resin		Black	
Durability (mating cycles max)		50	Email <u>productcompliance@molex.com</u> For a multiple part number RoHS Certificate Compliance, click here
Glow-Wire Compliant		No	
Lock to Mating Part		None	
Material - Metal		Phosphor Bronze	Compliance, <u>click here</u>
Material - Plating Mating		Gold	Please visit the <u>Contact Us</u> section for any
Material - Plating Termination		Tin	non-product compliance questions.
Material - Resin		High Temperature Thermoplastic	
Net Weight		1.464/g	
Number of Rows		2	
Orientation		Vertical	Search Parts in this Series
PC Tail Length		3.00mm	79107Series
PCB Locator		No	
PCB Retention		None	Mates With
PCB Thickness - Recommended		1.60mm	87758 Vertical, Through Hole, Stackable
Packaging Type		Tube	PCB Header, <u>87759</u> Vertical, Surface
Pitch - Mating Interface		2.00mm	Mount, Stackable PCB Header, 87760
Pitch - Termination Interface		2.00mm	Right Angle, Through Hole, Stackable PC
Plating min - Mating		0.762µm	Header, 87831 Vertical, Through Hole PC
Plating min - Termination Polarized to Mating Part		1.905µm	Header, <u>87832</u> Vertical, Surface Mount PC
Polarized to Mating Part Polarized to PCB		No No	
Surface Mount Compatible (SMC)		Yes	
Temperature Range - Operating		-55°C to +105°C	
Termination Interface: Style		Through Hole	
Electrical			
Current - Maximum p	er Contact	1.0A	
Voltage - Maximum		125V	

Solder Process Data

Duration at Max. Process Temperature (seconds) Lead-free Process Capability Max. Cycles at Max. Process Temperature Process Temperature max. C 10 Wave Capable (TH only) 1 260 Material Info

Reference - Drawing Numbers Product Specification Sales Drawing

PS-79107 SDA-79107-****

This document was generated on 05/14/2015 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF