Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83007 Hook-up/Lead - UL AWM Style 1213

For more Information please call

1-800-Belden1



Description:

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

Physical Characteristics (Overall)								
Conductor								
AWG:	_							
# Conductors AWG Stranding Conductor Material 1 20 19x32 SPC - Silver Plated Copped	er							
Insulation								
Insulation Material:								
Insulation Material Wall Thickness (mm) TFE - Tetrafluoroethylene 0.254								
Overall Insulation Overall Cabling								
Overall Nominal Diameter:	1.473 mm							
Applicable Specifications and Agency Com	nlianaa (Ovarall)							
Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs								
UL AWM Style:	1213							
UL Rating:	105°C							
EU CE Mark:	Yes							
EU Directive 2000/53/EC (ELV):	Yes							
EU Directive 2002/95/EC (RoHS):	Yes							
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005							
EU Directive 2002/96/EC (WEEE):	Yes							
EU Directive 2003/11/EC (BFR):	Yes							
CA Prop 65 (CJ for Wire & Cable):	Yes							
MII Order #39 (China RoHS):	Yes							
Military Specification:	MIL-W-16878/4 (Except For Stranding)							
MIL Spec Rating:	600 V, 200°C							
Flame Test								
UL Flame Test:	VW-1							
Plenum/Non-Plenum								
Plenum (Y/N):	No							
Related Documents:								
No related documents are available for this product								
Put Ups and Colors:								
Item # Putup Ship Weight	Color	Notes	Item Desc					
83007 001100 30 MT 0.181 KG	BROWN		#20 STR TFE BRN					

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

83007 Hook-up/Lead - UL AWM Style 1213

83007 0011000	305 MT	2.722 KG	BROWN	SW	#20 STR TFE BRN
83007 002100	30 MT	0.181 KG	RED		#20 STR TFE RED
83007 0021000	305 MT	2.722 KG	RED	SW	#20 STR TFE RED
83007 002500	152 MT	1.361 KG	RED	SW	#20 STR TFE RED
83007 003100	30 MT	0.181 KG	ORANGE		#20 STR TFE ORG
83007 0031000	305 MT	2.722 KG	ORANGE	SW	#20 STR TFE ORG
83007 004100	30 MT	0.181 KG	YELLOW		#20 STR TFE YEL
83007 0041000	305 MT	2.722 KG	YELLOW	SW	#20 STR TFE YEL
83007 005100	30 MT	0.181 KG	GREEN, DARK		#20 STR TFE GRNDK
83007 0051000	305 MT	2.722 KG	GREEN, DARK	SW	#20 STR TFE GRNDK
83007 006100	30 MT	0.181 KG	BLUE, LIGHT		#20 STR TFE BLULT
83007 0061000	305 MT	2.722 KG	BLUE, LIGHT	SW	#20 STR TFE BLULT
83007 006500	152 MT	1.361 KG	BLUE, LIGHT	SW	#20 STR TFE BLULT
83007 007100	30 MT	0.181 KG	VIOLET		#20 STR TFE VIO
83007 0071000	305 MT	2.722 KG	VIOLET	SW	#20 STR TFE VIO
83007 008100	30 MT	0.181 KG	GRAY		#20 STR TFE GRY
83007 0081000	305 MT	2.722 KG	GRAY	SW	#20 STR TFE GRY
83007 009100	30 MT	0.181 KG	WHITE		#20 STR TFE WHT
83007 0091000	305 MT	2.722 KG	WHITE	SW	#20 STR TFE WHT
83007 009500	152 MT	1.361 KG	WHITE	SW	#20 STR TFE WHT
83007 010100	30 MT	0.181 KG	BLACK		#20 STR TFE BLK
83007 0101000	305 MT	2.722 KG	BLACK	SW	#20 STR TFE BLK
83007 010500	152 MT	1.361 KG	BLACK	SW	#20 STR TFE BLK

Notes:

S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER10 W = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 75'

Revision Number: 1 Revision Date: 05-14-2007

© 2011 Belden, Inc

All Rights Reserved.

described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the action belief at the date of the product product before the product because a part is because a part is because a part of This Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 8538-009-1000 ATFC0311-20-5D EF5675-000 BFWUL3239-24-PINK 22759/34-16-9CS2621 22759/42-24-9CS2620 933205-000 284711-000 961473-000 30802-009-250 30808-010-500 30810-010-500 99M0111-20-2 A00594-000 190571-000 22759/41-12-9CS2620 22759/41-16-9CS2620 22759/43-10-9CS2873 265925-000 CM9524-000 CMC-0553-1-9 31510-010-250 31514-009-500 32412-009-500 34401-010-250 34402-010-500 M81044/9-4-9 391441-BK007 400R0111-10-9 431660-000 ATFC0311-20-0 ATFC0311-20-3 44/7024-26-9-9 44A0112-22-9CS3184 456157-000 BFW-UL3239-24-WHITE 55/0312-26-6L-CS2570 55A0811-12-9 55A6087-20-9-99 55A6315-22-9-9CS2632 55A7400-22-9/96-9CS2275 55A9002-30-5 55PC0211-20-5CS2502 55PC0811-6-9CS2637 55PC1211-22-9CS3278