

This document was generated on 05/21/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 87832-0621

Status: Active

Overview: Milli-Grid™ Connector System

Description: Milli-Grid[™] Header, Surface Mount, Vertical, Shrouded, Lead-Free, 6 Circuits, 0.76μm

Gold (Au) Plating, without Locking Window and Centre Polarization Slot, PCB Locator,

Tube

Documents:

<u>3D Model</u> <u>Product Specification PS-87831-027 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>87832</u>

Application Signal, Wire-to-Board

Comments Without Cap|Contact Molex for application in automotive

Yes

industry

Overview Milli-Grid™ Connector System

Product Name Milli-Grid™ UPC 822348352036

Physical

Breakaway No Circuits (Loaded) 6 Circuits (maximum) 6 Color - Resin Black Durability (mating cycles max) 100 First Mate / Last Break No 94V-0 Flammability Glow-Wire Compliant No Guide to Mating Part No Keying to Mating Part Yes Lock to Mating Part Yes

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin Material - Resin Nylon Net Weight 0.311/gNumber of Rows Orientation Vertical **PCB** Locator Yes **PCB** Retention None Packaging Type Tube Pitch - Mating Interface 2.00mm Pitch - Termination Interface 2.00mm Plating min - Mating 0.762µm Plating min - Termination 1.905µm Polarized to PCB No Shrouded **Fully** Stackable No

Temperature Range - Operating -55°C to +105°C

Surface Mount Compatible (SMC)



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series 87832Series

Mates With

Wire-to-Board Terminals <u>50394</u>, Wire-to-Board Crimp Housing <u>51110</u>, Wire-to-Board IDT Housings <u>87568</u>, Board-to-Board Top Entry Through Hole Receptacle <u>79107</u>, Board-to-Board FFC/FPC Top Entry Through Hole Receptacle <u>79108</u>, Board-to-Board Surface Mount PCB Receptacle <u>79109</u>

Termination Interface: Style Surface Mount

Electrical

Current - Maximum per Contact 2.0A Voltage - Maximum 125V

Solder Process Data

Duration at Max. Process Temperature (seconds) 10

Lead-free Process Capability Reflow Capable (SMT only)

Max. Cycles at Max. Process Temperature 1
Process Temperature max. C 260

Material Info

Reference - Drawing Numbers

Product Specification PS-87831-027 Sales Drawing SD-87832-007

This document was generated on 05/21/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF