

This document was generated on 02/02/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0908143710

Status: **Active**

Picoflex® Connectors **Overview:**

Picoflex® PF-50 Header without PCB Pegs, Vertical, Low Profile, Surface Mount, PdNi **Description:**

with Gold Flash Plating, 10 Circuits, Natural

Documents:

Product Specification PS-99020-0011 (PDF) 3D Model **Drawing (PDF)** RoHS Certificate of Compliance (PDF)

Agency Certification

E29179

General

Product Family PCB Headers

Series 90814

Signal, Wire-to-Board Application

Application Tooling Part Link 69008-1070 Comments Low Profile

Overview Picoflex® Connectors

Product Name Picoflex® **UPC** 800756883755

Physical

Breakaway No Circuits (Loaded) 10 Circuits (maximum) 10 Color - Resin Natural Durability (mating cycles max) 100 First Mate / Last Break No Flammability 94V-0 **Glow-Wire Compliant** No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Material - Metal **Brass**

Material - Plating Mating Gold over Palladium Nickel Material - Resin High Temperature Thermoplastic

1.60mm

Yes


Net Weight 0.632/gNumber of Rows Orientation Vertical PCB Locator Nο **PCB** Retention Yes

PCB Thickness - Recommended

Packaging Type Adhesive Tape on Reel

Pitch - Mating Interface 1.27mm Pitch - Termination Interface 1.27mm Plating min - Mating 0.762µm Plating min - Termination 0.102µm Polarized to Mating Part Yes Polarized to PCB No Shrouded No Stackable Nο

Surface Mount Compatible (SMC) Temperature Range - Operating -40°C to +105°C Termination Interface: Style Surface Mount



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant REACH SVHC Contains SVHC(2014 December 17): No **Halogen-Free**

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS Green Image ELV Not Relevant

Search Parts in this Series

90814 Series

Mates With

90327 IDT Connector

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # **Extraction Tool** 0690081070

(Plastic) for 4-26

Circuit

Electrical

Current - Maximum per Contact 2.4A

Voltage - Maximum 250V AC/DC

Material Info

Reference - Drawing Numbers

Product Specification PS-99020-0011 Sales Drawing SDA-90814

This document was generated on 02/02/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF