

Female headers soldering technique

□ 0.025", can be plugged-in from above and below

<p>BL 11</p>	<p>SL 13 SL 14</p>	<p>BL 12</p>	
<p>art. no.</p>	<p>dimensions [mm]</p> <p>A</p>		
<p>BL 11 254 ...</p>	<p>2.54</p>		
<p>BL 11 508 ...</p>	<p>5.08</p>		
<p>art. no.</p>	<p>dimensions [mm]</p> <p>A</p>		
<p>BL 12 650 ...</p>	<p>6.50</p>		
<p>BL 12 762 ...</p>	<p>7.62</p>		
<p>please indicate:</p>		<p>... no. of contacts one row 1-45 two rows 2-64</p>	<p>... surface S =selective gold-plated Z =tin-plated</p>

packed: bar magazine

Stamped contact spring.

Can be cut! Every desired number of contacts can be delivered.

Technical data PCB connectors

	BL 11
Contact material: shell	CuSn-alloy
Contact surface of the shell: gold/tin	selective: Ni + 0,2 µm Au fin: Ni + 4 µm Sn
Contact spring: material/surface	slotted contact: see above
Transition resistance:	≤ 20 mOhm
Shock resistance:	
Vibration resistance max.:	
Capacity between two adjacent contacts:	≤ 0,9 pF
Current rating:	3 A
Nominal voltage:	250 V AC
Test voltage:	500 V
Insulator: material	PA 4,6, GF
Temperature range:	-40 °C ... +163 °C (+260 °C 1 min.)
Flammability class:	UL 94 V-0
Insulation resistance:	> 10 ¹² Ohm
Plugability for pins:	□ 0,6 ... 0,65 mm
Insertion depth for pins:	from top: 5 mm from below: 10 mm
Insertion/Extraction, type:	1,5 N/0,5 N

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [FFC & FPC Connectors](#) category:

Click to view products by [Fisher](#) manufacturer:

Other Similar products are found below :

[HFW11R-1STE1H1LF](#) [FH29B-100S-0.2SHW\(99\)](#) [FA5S008HP1](#) [FH29B-120S-0.2SHW\(99\)](#) [FH29B-80S-0.2SHW\(99\)](#) [FHS-16](#) [FPH-2022G](#)
[52610-1075](#) [52610-1275](#) [52610-1934](#) [XF3M\(1\)-1415-1B-R100](#) [501864-3091-TR225](#) [0525594033](#) [086210010340800](#) [086222026001800](#)
[52271-2869-CUT-TAPE](#) [62674-201121DLF](#) [62684-36210E9ALF](#) [52610-1675](#) [52746-1671-TR250](#) [10051922-2810EHLF](#) [6-520415-9](#)
[BD021-09A-A1-0350-0200-0550-LD](#) [SFV6R-1STE9HLF](#) [XF3M-2915-1B-R100](#) [1658549-1](#) [62674-221121ALF](#) [46214008010800](#)
[046298003000883](#) [151660622](#) [842-816-2630-035](#) [AYF530665TA](#) [AYF351525](#) [046296011930846+](#) [AYF352325A](#) [046254020000800+](#)
[FH19C-13S-0.5SH\(99\)](#) [FH39J-51S-0.3SHW\(99\)](#) [AYF355125A](#) [AYF530365TA](#) [FH29B-44S-0.2SHW\(99\)](#) [SFW5R-2STAE9LF](#) [AYF351125A](#)
[AYF350725A](#) [62684-502100AHLF](#) [FH39-61S-0.3SHW\(99\)](#) [AYF414035A](#) [10064555-172520HLF](#) [AYF212335A](#) [504754-2500](#)