


U.I. Lapp GmbH	PRODUCT INFORMATION	
	ÖLFLEX® 550 P*	14.11.2013

PUR power cords with European harmonisation (HAR)

Harmonised use in Europe

Increased durability under harsh conditions thanks to robust PUR outer sheath

Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media

Wide temperature range for applications in harsh climatic environments

The signal colour of the outer sheath increases safety and visual perception



Suitable for outdoor use



Cold-resistant



Mechanical resistance



Oil-resistant

Info

High mechanical strength

Good oil resistance

H05BQ-F/H07BQ-F design standard

Application range

Portable handheld electrical devices such as drills, sanders, jig saws or grinders

Building sites, camp sites, stage applications

Construction machinery

Agricultural equipment

For indoor and outdoor use

Design

Fine-wire strand made of bare copper wires


Core insulation: rubber compound

Cores twisted together

PUR outer sheath

Sheath colour: orange

Product Management	Document: LAPP_PRO44EN.pdf	1 / 3
--------------------	----------------------------	-------

U.I. Lapp GmbH	PRODUCT INFORMATION	
ÖLFLEX® 550 P*		14.11.2013

Norm references / Approvals

EN 50525-2-21
H05BQ-F/H07BQ-F design standard

Product features

Oil-resistant
Abrasion and notch-resistant
Flexible down to -40 °C
Resistant to hydrolysis and microbes

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

* Trade product, no Lapp product

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Core identification code:	Colours according to VDE 0293-308, refer to Appendix T9
Specific insulation resistance:	> 10 GOhm x cm
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius:	For flexible use: 12.5 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	Up to 1.0 mm ² : U ₀ /U: 300/500 V From 1.5 mm ² : U ₀ /U: 450/750 V
Test voltage:	3000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Occasional flexing: -40 °C to +90 °C Fixed installation: -50 °C to +90 °C

Product Management	Document: LAPP_PRO44EN.pdf	2 / 3
--------------------	----------------------------	-------

Part number	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)
ÖLFLEX® 550 P U ₀ /U: 300/500 V			
0013600	2 X 0,75	5,7 - 7,4	14.4
0013601	3 G 0,75	6,2 - 8,1	21.6
00136023	4 G 0,75	6,8 - 8,8	28.8
00136033	5 G 0,75	7,6 - 9,9	36.0
0013610	2 X 1,0	6,1 - 8	19.2
0013611	3 G 1,0	6,5 - 8,5	29.0
00136123	4 G 1,0	7,1 - 9,3	38.4
00136133	5 G 1,0	8 - 10,3	48.0
ÖLFLEX® 550 P U ₀ /U: 450/750 V			
0013620	2 X 1,5	7,6 - 9,8	29.0
0013621	3 G 1,5	8 - 10,4	43.0
00136223	4 G 1,5	9 - 11,6	58.0
00136233	5 G 1,5	9,8 - 12,7	72.0
0013630	2 X 2,5	9 - 11,6	48.0
0013631	3 G 2,5	9,6 - 12,4	72.0
00136323	4 G 2,5	10,7 - 13,8	96.0
00136333	5 G 2,5	11,9 - 16,3	120.0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[M27500-20SP2S23](#) [M3905-BK005](#) [6502FE 8771000](#) [CV6807-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [720451-000](#) [752687-000](#) [83709-002-1000](#) [8469 060100](#) [877541-000](#) [88444-002-1000](#) [9444 060U1000](#) [9497 0001000](#) [9684-060-1000](#) [1302110032](#) [EPD6062-12-9CS1693](#) [EPD-RWC-10972](#) [EPD-RWC-12305](#) [C35473-000](#) [2020D1301-9](#) [219538-6](#) [2412F-010-1000](#) [9534 060U500](#) [29531-010-2000](#) [22759/41-22-9CS2620](#) [259633-000](#) [29529C-010-2000](#) [29532-010-1500](#) [302595-000](#) [CTC-0018-22-9/5-9CS2340](#) [3600B/50 100SF](#) [3644B/16-100SF](#) [CXA-0078-20-3-9CS2405](#) [CXA-0092-14-6/9CS2973](#) [MC6A-16/0.2T2-YWGN](#) [44A0211-20-9CS3030](#) [44A0311-12-9-F871](#) [44A1221-14-9/9-9CS3030](#) [44A1221-16-9/9-9CS3030](#) [44A1321-14-9/9-9CS3030](#) [44A9685-0-F957CS2855](#) [506087-000](#) [5102UE 008500](#) [5201UE 0081000](#) [534553-000](#)