



- CONNECTOR MATES WITH ANY 9 POSN PLUG IN AMPLIMITE™ SERIES & COMPLIES WITH AMP SPEC 108-40005 WHERE APPLICABLE.
- MOLDED PARTS: FLAME RETARDANT 94V-0 RATED THERMOPLASTIC, BLACK.
SHELL: STEEL PER ASTM A109
CONTACTS: PHOSPHOR BRONZE PER QQ-B-750
EYELETS: BRASS
SCREWLOCKS: ZINC
INSERTS: ZINC
- SHELL: BRIGHT TIN PLATED
CONTACTS: SEE TABLE
EYELETS: TIN PLATED
SCREWLOCKS: CLEAR CHROMATE
INSERTS: CLEAR CHROMATE
- GOLD PLATING PER MIL-G-45204, NICKEL PLATING PER OO-N-290, TIN PER MIL-T-10727.
- GOLD FLASH FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON SOLDER POST, ALL OVER .000050 NICKEL.
- .000030 GOLD FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON SOLDER POST, ALL OVER .000050 NICKEL.
- .000015 MIN GOLD FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON SOLDER POST, ALL OVER .000050 NICKEL.

OBSOLETE	FEMALE SCREWLOCKS	CLINCH TABS (SEE DETAIL L)	7	1-745988-8
OBSOLETE	THREADED INSERTS	CLINCH TABS (SEE DETAIL L)	7	1-745988-7
OBSOLETE	.125 DIA HOLE	CLINCH TABS (SEE DETAIL L)	7	1-745988-6
OBSOLETE	FEMALE SCREWLOCKS	GROUNDING STRAPS	7	1-745988-5
SUPSD BY 745988-4	THREADED INSERTS	GROUNDING STRAPS	7	1-745988-4
OBSOLETE	.125 DIA HOLE	GROUNDING STRAPS	7	1-745988-3
OBSOLETE	FEMALE SCREWLOCKS	CLINCH TABS (SEE DETAIL L)	6	1-745988-2
OBSOLETE	FEMALE SCREWLOCKS	CLINCH TABS (SEE DETAIL L)	5	1-745988-1
SUPSD BY 745988-4	THREADED INSERTS	CLINCH TABS (SEE DETAIL L)	6	1-745988-0
OBSOLETE	THREADED INSERTS	CLINCH TABS (SEE DETAIL L)	5	745988-9
OBSOLETE	.125 DIA HOLE	CLINCH TABS (SEE DETAIL L)	6	745988-8
OBSOLETE	.125 DIA HOLE	CLINCH TABS (SEE DETAIL L)	5	745988-7
OBSOLETE	FEMALE SCREWLOCKS	GROUNDING STRAPS	6	745988-6
SUPSD BY 745988-6	FEMALE SCREWLOCKS	GROUNDING STRAPS	5	745988-5
	THREADED INSERTS	GROUNDING STRAPS	6	745988-4
SUPSD BY 745988-4	THREADED INSERTS	GROUNDING STRAPS	5	745988-3
OBSOLETE	.125 DIA HOLE	GROUNDING STRAPS	6	745988-2
OBSOLETE	.125 DIA HOLE	GROUNDING STRAPS	5	745988-1

MOUNTING HARDWARE	SHELL VERSION	CONTACT FINISH 4	PART NUMBER
-------------------	---------------	------------------	-------------

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN: J. GALLUCCI BG 1-23-91	APVD: R. STONE 04/26/91	TYCO Electronics	Tyco Electronics Corporation Harrisburg, PA 17105-3608
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005	4 PLC ± .005	ANGLES ± .2°
MATERIAL	FINISH	SIZE: A1	DWG NO: 00779	DRAWING NO: 745988	RESTRICTED TO: -
CUSTOMER DRAWING		SCALE: 4:1	SHEET: 1 OF 1	REV: T	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [D-Sub Standard Connectors](#) category:

Click to view products by [TE Connectivity](#) manufacturer:

Other Similar products are found below :

[DCM37S732N](#) [DAM15P500](#) [DEV09S364GTLF](#) [DEM09P032N](#) [DDM50P732N](#) [DAM15S332N](#) [173109-2218](#) [173109-2466](#) [173109-2436](#)
[173109-2435](#) [56F706-005-LI](#) [56F711-015](#) [015-0341-000](#) [015-0372-008](#) [015-8544-011](#) [017041-0005](#) [020419-0104](#) [012-0515-000](#) [012-9507-](#)
[034](#) [012-9507-114](#) [012-9534-001](#) [020745-0008](#) [609-25P](#) [M24308/2-23Z](#) [M243082310F](#) [M243082410F](#) [M243082411F](#) [M24308/4-21](#)
[CT1A18-11PSA206](#) [CT1N36-5SC](#) [CT2-16S-17PS](#) [CT2-20-15PCAU](#) [CT2-24-12PS](#) [CT2-24-28PSF127A206](#) [CT2-32-9PC](#) [CT6F9767-14-4-](#)
[14S-5PC](#) [CT6FA10SL-4PS](#) [CT7-18-10SC](#) [CT7-18-10SCAU](#) [CT7-18-12SCAU](#) [CT7-18-1PC](#) [CT7-18-1PCAU](#) [CT7-18-21SCAU](#) [M83513/01-](#)
[FC](#) [M83723/76W24619 L/C](#) [M85049/48-3-2F](#) [69001-865](#) [6STD09PCM99B70X](#) [6STD09SCM99B30X](#) [6STD09SCT99S40X](#)