

FLORENTINA-HLD-M

~30° medium beam

TECHNICAL SPECIFICATIONS:


Dimensions	285.6 x 19.5 mm
Height	9.5 mm
Fastening	screw
Colour	black
Box size	398 x 298 x 140 mm
Box weight	5.2 kg
Quantity in Box	160 pcs
ROHS compliant	yes 🛈



MATERIAL SPECIFICATIONS:

Component TINA2-XP-M FLORENTINA-HLD **Type** Single lens Holder Material PMMA PC **Colour** clear black

PRODUCT DATASHEET CP14994_FLORENTINA-HLD-M



R

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



CREE C LED FWHM Efficiency Peak intensity Required comp C14446_FLC	XP-E2 29.0° 81 % 3.280 cd/lm	
		90°
LED FWHM Efficiency Peak intensity Required comp	XP-G2 29.0° 82 % 2.900 cd/lm	
🕑 LG Innot	tek	504
LED FWHM Efficiency Peak intensity Required comp	H35C1 (LEMWA33) 28.0° 79 % 2.830 cd/lm	
UMIL	EDS	90°
LED FWHM Efficiency Peak intensity Required comp C14446_FLC		



	.EDS	50 ⁴
LED	LUXEON Rebel Plus	70.
FWHM	26.0°	
Efficiency	80 %	60* 60*
Peak intensity	3.300 cd/lm	
Required comp	oonents:	
C14446_FL0	ORENTINA-SHD	200
		30 ⁶ 220 15 ⁹ 0 ⁴ 15 ⁹
	EDS	90 ⁴ 99 ⁴
LED	LUXEON TX	781
FWHM	28.0°	
Efficiency	79 %	60* 60*
Peak intensity	3.000 cd/lm	
Required comp	oonents:	er er
C14446_FL0	ORENTINA-SHD	2400
		30- 30- 30-
UMIL	.EDS	90 ⁴ 90 ⁴
LED	LUXEON Z ES	75
FWHM	26.0°	
Efficiency	81 %	
Peak intensity	3.500 cd/lm	
Required comp	oonents:	er (200
C14446_FL0	ORENTINA-SHD	
		3390
		305 07 350
ØNICHI/		50° 50°
LED	NCSxE17A	75
FWHM	27.0°	
Efficiency	77 %	
Peak intensity	3.000 cd/lm	1600
Required comp	oonents:	97 D
C14446_FL0	ORENTINA-SHD	000
		30° <u>200</u> to 30°
		10 0, 20,



Ø NICHI∧		50°
LED	NCSxx19B	77
FWHM	28.0°	
Efficiency	79 %	61°
Peak intensity	2.900 cd/lm	
Required comp	onents:	× / · · · · ·
C14446_FLC	RENTINA-SHD	
		30° 35° 35° 35°
ØNICHI		83. Bb
LED	NF2x757G	
FWHM	29.0°	
Efficiency	77 %	6
Peak intensity	2.600 cd/lm	
Required comp	onents:	9° - 160 - 47
C14446_FLC	RENTINA-SHD	
ØNICHI		99* 99*
LED	NVSxx19B/NVSxx19C	
FWHM	29.0°	
Efficiency	77 %	60°
Peak intensity	2.600 cd/lm	
Required comp	onents:	
C14446_FLC	RENTINA-SHD	
		200
		200
OSRAM Opto Semiconductors		24
LED	Oslon Square EC	
FWHM	28.0°	
Efficiency	78 %	evev.
Peak intensity	2.900 cd/lm	
Required comp	onents:	
C14446_FLC	RENTINA-SHD	
1		
		20




OSRAM Opto Semiconductors		90° 90°
LED	Oslon SSL 150	75-
FWHM	27.0°	
Efficiency	83 %	60,+
Peak intensity	3.200 cd/lm	
Required comp	onents:	43°
		202
		36* 35 0* 35*
OSRAM Opto Semiconductors		50° 50°
LED	Oslon SSL 150	75'
FWHM	28.0°	
Efficiency	80 %	60* 60*
Peak intensity	3.300 cd/lm	
Required comp	onents:	e., e.
C14446_FLC	RENTINA-SHD	242
		36* 30*
OSRAM Opto Semiconductors		90° 90° 90°
LED	Oslon SSL 80	75'
FWHM	26.0°	20
Efficiency	76 %	60*
Peak intensity	2.930 cd/lm	
Required comp	onents:	
C14446_FLC	RENTINA-SHD	
		30° 30° 30°
S ΛΜSΙ	ING	80 ⁶ 90 ⁶
LED	LH351B	
FWHM	28.0°	
Efficiency	79 %	60°
Peak intensity		
Required comp		47" - <u>1600</u>
	RENTINA-SHD	$ \times / / \times $
		300
		30*
		15° 0° 15°



TOSHIBA Leading Innovation >>>

Ecolority innovation w			
TL1L4			
27.0°			
76 %			
2.840 cd/lm			
Required components:			
C14446_FLORENTINA-SHD			







PHOTOMETRIC DATA (SIMULATED):

ΜΝΙCΗΙΛ


 LED
 NWSx229A

 FWHM
 30.0°

 Efficiency
 82 %

 Peak intensity
 2.290 cd/lm

 Required components
 C14446_FLORENTINA-SHD





GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Lighting Lenses Assemblies category:

Click to view products by Ledil manufacturer:

Other Similar products are found below :

FCN12592_LE1-D-COP_CA11362_IRIS_CA16127_OLGA-S_CP16107_CARMEN-50-S-C_CS15763_STRADA-2X2MX-8-VSM C17171_DAISY-8X1-SHD-MATT_C17172_DAISY-8X1-SHD-MATT-WHT_C17173_DAISY-4X1-WW-US_C17341_DAISY-4X1-WW-US-D_CS15759_HB-2X2MX-8-W_CS15769_STRADA-2X2MX-8-T2-S_CA16435_LXP2-SS-WAS_CS13756_STRADA-IP-2X6-DWC-PC CN16210_GABRIELLA-MIDI-W_CP17138_CARMEN-M2-C-WHT_CP17137_CARMEN-M2-C_CA16015_STRADA-SQ-SCL C16989_DAISY-7X1-W2_C17225_DAISY-7X1-SHD-WHT-MATT_C17296_ILONA-ZOOM-SUB_FP15752_STRADA-2X2MX8-T3 C16590_DAISY-4X1-SHD_FP16562_LISA3-WWW-PIN_CX15819_GABRIELLA-45-W_C16870_DAISY-7X1-WW_CP12939_LARISA-RS-CLIP16_C14636_XTM-PF-ADAPTER_CA14506_G2-LXP2-RS2_CA14508_G2-LXP2-D_FCP13895_SEANNA-A_FN14637_OLIVIA-S CP12943_LARISA-O-CLIP16_FP11124_LISA2-O-PIN_CP10444_LISA-SS_CS14597_HB-IP-2X6-O_CP14995_FLORENTINA-HLD-O CA16128_OLGA-M_CP14994_FLORENTINA-HLD-M_CP15775_CARMEN-M-C_CS15158_STRADA-IP-2X6-T4-B_CS15363_STRADA-IP-2X6-T2-B_CS15751_STRADA-2X2MX-8-DWC_CS15886_STRADA-IP-2X6-T2-B-90_CS16323_STRADELLA-IP-28-HB-M FN14976_STELLA-DWC2_FN15264_STELLA-HB-WWW_FN15966_RONDA-WWW-C_FN15971_RONDA-WAS-C_FP15073_ZORYA-SC-B_CA15584_ZORYA-MINI-TAPE