


Product **Polzahl: 5 Stereo, Winkelstecker, Kabeldurchlass 4 – 6 mm, Kunststoffausführung, versilberte Kontakte**
 Area **M16 IP40 Series 682**
 Article number **09 0141 70 05**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	3,50	0,00
2	0,00	3,50
3	-3,50	0,00
4	2,47	2,47
5	-2,47	2,47

You can find the item description on the next page.

Technical data

General features

Connector Design	male angled connector
Connector locking system	bolted
Termination	solder
Wire gauge (mm)	0,75 mm ²
Wire gauge (AWG)	20
Cable outlet	4 – 6 mm
Upper temperature	85 °C
Lower temperature	-40 °C

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	500 V
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	6 A
Volume resistivity	≤ 5 mΩ
EMV compliance	not shielded
Degree of protection	IP40

Material

Material of contact	CuZn (Messing)
Contact plating	Ag (silver)
Material of contact body	PBT (UL 94 V-0)

Product **Polzahl: 5 Stereo, Winkelstecker, Kabeldurchlass 4 – 6 mm, Kunststoffausführung, versilberte Kontakte**
Area **M16 IP40 Series 682**
Article number **09 0141 70 05**

Item description

