

UNITRONIC® SENSOR HD M12

S/A cable: Hygienic Design for Food&Beverage

4-pos. Sensor/actuator cable in Hygienic Design for food& beverage with M12 thread and stainless steel (V4A), high protection class IP65/IP67/IP68/IP69

Info

IP69 for high-pressure cleaning
- 40 °C to + 105 °C



Waterproof



Temperature-resistant



Power chain



Corrosion-resistant



Halogen-free



Mechanical and plant engineering



Food & Beverage



Cold-resistant

Last Update (17.09.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

UNITRONIC® SENSOR HD M12

Benefits

Hygienic Design for ideal cleaning results
Guaranteed density by meeting the highest protection class
Stainless steel knurl to ensure protection against corrosion
Bright colors to detect contamination quickly

Application range

Food production and packaging machinery
Freezing plants, cold storage
washdown area with frequent contact
with cleaning agents

Product features

Suitable for drag chains
4-pin plug/socket M12 on free conductor end

Norm references / Approvals

ECOLAB®
Industry standard in the field of professional cleaning and disinfection in the food and beverage industry
FDA 21 CFR 177.2600
Special sealing element for food and beverage industry in North America

Product Make-up

wire cross-section: 0,34 mm²
Colour-code:
4-pin: bn (1), wh (2), bu (3), bk (4)
Outer sheath: TPE halogen-free,
grey (similar to RAL 7035)

Technical Data

Classification:	ETIM 5.0 Class-ID: EC001855 ETIM 5.0 Class-Description: Sensor-actuator patch cord
Material:	Contact: CuSn Contact surface: Ni/Au Knurl: Stainless steel (V4A) Gripping body: PP
Minimum bending radius:	Fixed installation: 5 x outer diameter Flexing: 10 x outer diameter
Protection rating:	IP65/IP67/IP68/IP69
Ambient temperature (operation):	Fixed installation -40°C to +105°C Flexing -25°C to +105°C
Coding:	A-standard
Rated current (A):	4 A

UNITRONIC® SENSOR HD M12

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**UNITRONIC® SENSOR HD M12**

Article number	Article designation	Number of pins	Length (m)	Design	LED	Rated voltage (V)
22262040	AB-C4-M12MS-2,0TPE-HD	4	2	straight	no	250
22262041	AB-C4-M12MS-5,0TPE-HD	4	5	straight	no	250
22262060	AB-C4-M12MS-7,5TPE-HD	4	7.5	straight	no	250
22262042	AB-C4-M12MS-10,0TPE-HD	4	10	straight	no	250
22262061	AB-C4-M12MS-15,0TPE-HD	4	15	straight	no	250
Socket						
22262043	AB-C4-2,0TPE-M12FS-HD	4	2	straight	no	250
22262044	AB-C4-5,0TPE-M12FS-HD	4	5	straight	no	250
22262062	AB-C4-7,5TPE-M12FS-HD	4	7.5	straight	no	250
22262045	AB-C4-10,0TPE-M12FS-HD	4	10	straight	no	250
22262063	AB-C4-15,0TPE-M12FS-HD	4	15	straight	no	250
22262046	AB-C4-2,0TPE-M12FA-HD	4	2	angled	no	250
22262047	AB-C4-5,0TPE-M12FA-HD	4	5	angled	no	250
22262064	AB-C4-7,5TPE-M12FA-HD	4	7.5	angled	no	250
22262048	AB-C4-10,0TPE-M12FA-HD	4	10	angled	no	250
22262065	AB-C4-15,0TPE-M12FA-HD	4	15	angled	no	250

Last Update (17.09.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16