

FlexTemp 2311 Universal Transmitter

4...20 mA transmitter

RTD, T/C, mV and R inputs

Isolation voltage 2 kV_{ac}

Configuration via FlexProgrammer

Accuracy better than 0.1°C (Pt100)

Configurable linearisation,
damping and status indication

Local, remote or fixed compensation
for "cold junction" (CJC)



Description

FlexTemp 2311 is a 4...20 mA loop-powered, configurable universal transmitter with galvanic isolation between input and output. The input can be configured for RTD or T/C sensors, resistance, current or voltage signals.

Either 2-, 3- or 4-wire connection can be selected for the resistance input. The built-in temperature sensor or a remote Pt100 sensor can be used to compensate for "cold junction" (CJC) if thermocouples are connected.

The configuration can be established from the dedicated FlexProgrammer configuring tool connected to a PC.



Technical Data

Input		Environmental conditions	
Digital accuracy	See „Measuring ranges“	Operating temperature	-40...85°C
CJC-compensation {1}	Local < 0.7°C	Storage temperature	-55...90°C
RTD measuring current	0.2 mA, continuously	Humidity	< 90% RH, non-condensing
Cable resistance		Vibrations	Lloyds Register, test 2
2-wire	Max. 30 Ohm/wire {1}	EMC data	
3-/4-wire	T > 600°C: Max. 10 Ohm/wire	Generic standards	EN 61000-6-3, EN61000-6-2
3-/4-wire	T < 600°C: Max. 30 Ohm/wire	Product standard	EN 61326
Protection	+/- 35 V _{dc}	Disposal of product and packing	
Suppression	50 and 60 Hz	According to national laws or by returning to Baumer	
Resolution	16 bit	Mechanical data	
Repeatability	< 0.05°C	Dimensions	62 x 88 x 24 mm
Output		Protection class	Housing: IP 30; Terminals: IP 10
Signal span	4...20 mA, 2-wire {1}	Other data	
	20...4 mA, 2-wire {1}	Isolation	50 V _{ac} ; test 2 kV _{ac}
Characteristic	Linear or customised with max. 30 points {1}	Temperature drift	Typ. 0.003% per °C
Accuracy	< 0.1% of signal span		Max. 0.01% per °C
Supply range	6.5...35 Vdc	Power-on time	1.8...3.9 sec.
Ripple immunity	3 V _{rms}	Failure information	NE43
Load equation	R _L ≤ (V _{cc} - 6.5)/23 [kOhm]	Test conditions	
Up/Down scaling limits	23 mA/3.5 mA {1}	Configuration	Pt100; 0...100°C
Damping	0...30 sec. {1}	Amb. temperature	23°C +/- 2°C
Response time (t ₉₀)	Pt100 1.0 sec.; T/C 1.6 sec.	Note	
Resolution	12 bit	{1} Configurable	
		{2} The max. temperature is lower for RTD-elements in the range 500...1000, i.e. Pt1000 max. 350°C.	


Measuring Ranges

Type	Standard	Range	Min. span	Accuracy	Resolution
Pt25...Pt1000	DIN/EN/IEC 60751	-200...850°C {2}	10°C	0.1°C	0.1°C
Pt25...Pt1000	a = 0.003902	-200...850°C {2}	10°C	0.1°C	0.1°C
Pt25...Pt1000	a = 0.003916	-200...850°C {2}	10°C	0.1°C	0.1°C
Ni25...Ni1000	DIN 43760	-50...250°C {2}	10°C	0.1°C	0.1°C
Cu25...Cu1000	0.428 Ohm/°C	-50...200°C	10°C	0.1°C	0.1°C
B(PtRh30-Pt)	IEC 584	100...1820°C	50°C	2°C	0.1°C
E(NiCr-CuNi)	IEC 584	-270...900°C	50°C	1°C	0.1°C
J(Fe-CuNi)	IEC 584	-210...1200°C	50°C	1°C	0.1°C
K(NiCr-Ni)	IEC 584	-250...1370°C	50°C	1°C	0.1°C
L(Fe-CuNi)	DIN 43710	-200...900°C	50°C	1°C	0.1°C
N(NiCrSi-NiSi)	IEC 584	-200...1300°C	50°C	1°C	0.1°C
R(PtRh13-Pt)	IEC 584	-50...1750°C	100°C	2°C	0.1°C
S(PtRh10-Pt)	IEC 584	-50...1750°C	100°C	2°C	0.1°C
T(Cu-CuNi)	IEC 584	-250...400°C	40°C	1°C	0.1°C
U(Cu-CuNi)	DIN 43710	-200...600°C	50°C	1°C	0.1°C
W5-Re (Type C)	ASTM 988	0...2300°C	100°C	2°C	0.1°C
W3-Re (Type D)	ASTM 988	0...2300°C	100°C	2°C	0.1°C
Lin. voltage		-10...70 mV	2 mV	0.04 mV	0.1 mV
Lin. voltage		-0.1...1.1 V	20 mV	0.4 mV	1 mV
Lin. resistance		0...390 Ohm	5 Ohm	0.05 Ohm	0.01 Ohm
Lin. resistance		0...2200 Ohm	25 Ohm	0.25 Ohm	0.1 Ohm

Ordering Details - FlexTemp 2311

Type	Standard version	2311 000x (x)
Configuration	Configuration according to customer specifications	5...8' digit 1 9' digit C

Application Example




FlexTemp 2301

Power supply


Configuration

Note:


Disconnect loop supply before connecting the FlexProgrammer to FlexTemp 2311.



FlexProgrammer


















FlexProgrammer 9701



Note: Ambient temperature range 0...50°C

Electrical Installation

RTD	T/C	Potentiometer	Resistance
			
No cable-compensation {3}	Internal CJC-compensation	No compensation {3}	No compensation {3}
RTD	T/C	Potentiometer	Resistance
			
3-wire cable-compensation	External CJC-compensation No cable compensation {3}	3-wire compensation for transfer resistance {4}	3-wire cable compensation
RTD	T/C	Potentiometer	Resistance
			
4-wire cable-compensation	External CJC-compensation 3-wire cable compensation	4-wire compensation for transfer resistance {4}	4-wire cable compensation
Current measurement	Voltage measurement	Notes	
		{3} Configurable compensation for cable resistance {4} Transfer resistance between element and wiper	UK/2007-06-01 This data sheet may only be reproduced in full.
Accessories	Dimensional drawings		
			

The FlexProgrammer 9701 is a dedicated tool to configure all Baumer configurable products.

Type No. 9701-0001 complies:

- FlexProgrammer interface unit
- CD with the FlexProgram software and product drivers (DTM)
- USB cable
- Cable with 2 alligator clips