

SIMATIC S7-1200F, CPU 1214 FC, COMPACT CPU, DC/DC/DC,
ONBOARD I/O: 14 DI 24V DC; 10 DO 24 V DC; 2 AI 0 - 10V DC,
POWER SUPPLY: DC 20.4 - 28.8 V DC, PROGRAM/DATA
MEMORY 125 KB



| General information | |
|---|---|
| Product type designation | CPU 1214FC DC/DC |
| Firmware version | V4.2 |
| Engineering with | |
| <ul style="list-style-type: none"> Programming package | STEP 7 V14 or higher |
| Supply voltage | |
| Rated value (DC) | Yes |
| <ul style="list-style-type: none"> 24 V DC | Yes |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Load voltage L+ | |
| <ul style="list-style-type: none"> Rated value (DC) | 24 V |
| <ul style="list-style-type: none"> permissible range, lower limit (DC) | 20.4 V |
| <ul style="list-style-type: none"> permissible range, upper limit (DC) | 28.8 V |
| Input current | |
| Current consumption, max. | 1 500 mA; max. with all expansion accessories |
| Inrush current, max. | 12 A; at 28.8 V DC |
| I ² t | 0.5 A ² ·s |

| | |
|---|---|
| Output current | |
| for backplane bus (5 V DC), max. | 1 600 mA; Max. 5 V DC for SM and CM |
| Encoder supply | |
| 24 V encoder supply | |
| • 24 V | L+ minus 4 V DC min. |
| Power loss | |
| Power loss, typ. | 12 W |
| Memory | |
| Work memory | |
| • integrated | 125 kbyte |
| • expandable | No |
| Load memory | |
| • integrated | 4 Mbyte |
| • Plug-in (SIMATIC Memory Card), max. | with SIMATIC memory card |
| Backup | |
| • present | Yes |
| • maintenance-free | Yes |
| • without battery | Yes |
| CPU processing times | |
| for bit operations, typ. | 0.08 µs; / instruction |
| for word operations, typ. | 1.7 µs; / instruction |
| for floating point arithmetic, typ. | 2.3 µs; / instruction |
| CPU-blocks | |
| Number of blocks (total) | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB | |
| • Number, max. | Limited only by RAM for code |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 10 kbyte |
| Flag | |
| • Number, max. | 8 kbyte; Size of bit memory address area |
| Local data | |
| • per priority class, max. | 16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB |
| Address area | |
| I/O address area | |
| • Inputs | 1 024 byte |
| • Outputs | 1 024 byte |

| | |
|---|---|
| Process image | |
| • Inputs, adjustable | 1 kbyte |
| • Outputs, adjustable | 1 kbyte |
| Hardware configuration | |
| Number of modules per system, max. | 3 comm. modules, 1 signal board, 8 signal modules |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • Backup time | 480 h; typical; 12 days min. at 40 °C |
| • Deviation per day, max. | ±60 s per month |
| Digital inputs | |
| Number of digital inputs | 14 |
| • of which inputs usable for technological functions | 6; HSC (High Speed Counting) |
| Source/sink input | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 14; 14 inputs at 55 °C horizontal or 45 °C vertical |
| Input voltage | |
| • Rated value (DC) | 24 V; DC at 4 mA nominal |
| • for signal "0" | 5 V DC at 1 mA |
| • for signal "1" | 15 V DC at 2.5 mA |
| Input current | |
| • for signal "1", typ. | 4 mA; nominal |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 µs; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms |
| — at "0" to "1", min. | 0.1 µs |
| — at "0" to "1", max. | 20 ms |
| for interrupt inputs | |
| — parameterizable | Yes |
| for counter/technological functions | |
| — parameterizable | Yes; Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz |
| Cable length | |
| • shielded, max. | 500 m; 50 m for technological functions |
| • unshielded, max. | 150 m; For technological functions: No |
| Digital outputs | |
| Number of digital outputs | 10 |
| • of which high-speed outputs | 4; 100 kHz Pulse Train Output |

| | |
|--|-------------------------------|
| Short-circuit protection | No; to be provided externally |
| Switching capacity of the outputs | |
| <ul style="list-style-type: none"> with resistive load, max. | 0.5 A |
| <ul style="list-style-type: none"> on lamp load, max. | 5 W |
| Output voltage | |
| <ul style="list-style-type: none"> for signal "0", max. | 0.1 V; with 10 kOhm load |
| <ul style="list-style-type: none"> for signal "1", min. | 20 V |
| Output current | |
| <ul style="list-style-type: none"> for signal "1" rated value | 0.5 A |
| <ul style="list-style-type: none"> for signal "0" residual current, max. | 0.1 mA |
| Output delay with resistive load | |
| <ul style="list-style-type: none"> "0" to "1", max. | 1 µs |
| <ul style="list-style-type: none"> "1" to "0", max. | 3 µs |
| Switching frequency | |
| <ul style="list-style-type: none"> of the pulse outputs, with resistive load, max. | 100 kHz |
| Cable length | |
| <ul style="list-style-type: none"> shielded, max. | 500 m |
| <ul style="list-style-type: none"> unshielded, max. | 150 m |
| Analog inputs | |
| Number of analog inputs | 2 |
| Input ranges | |
| <ul style="list-style-type: none"> Voltage | Yes |
| Input ranges (rated values), voltages | |
| <ul style="list-style-type: none"> 0 to +10 V | Yes |
| <ul style="list-style-type: none"> Input resistance (0 to 10 V) | ≥100k ohms |
| Cable length | |
| <ul style="list-style-type: none"> shielded, max. | 100 m; twisted and shielded |
| Analog outputs | |
| Number of analog outputs | 0 |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. | 10 bit |
| <ul style="list-style-type: none"> Integration time, parameterizable | Yes |
| <ul style="list-style-type: none"> Conversion time (per channel) | 625 µs |
| Encoder | |
| Connectable encoders | |
| <ul style="list-style-type: none"> 2-wire sensor | Yes |
| 1. Interface | |
| Interface type | PROFINET |

| | |
|---|---|
| Physics | Ethernet |
| Isolated | Yes |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| • Number of ports | 1 |
| • integrated switch | Yes |
| Functionality | |
| • PROFINET IO Controller | Yes |
| • PROFINET IO Device | Yes |
| • SIMATIC communication | Yes |
| • Open IE communication | Yes |
| • Web server | Yes |
| • Media redundancy | Yes; as MRP client |
| PROFINET IO Controller | |
| • Transmission rate, max. | 100 Mbit/s |
| Services | |
| — PG/OP communication | Yes |
| — S7 routing | Yes |
| — Isochronous mode | No |
| — Open IE communication | Yes |
| — IRT | No |
| — MRP | No |
| — MRPD | No |
| — PROFlenergy | No |
| — Prioritized startup | Yes |
| — Number of IO devices with prioritized startup, max. | 16 |
| — Number of connectable IO Devices, max. | 16 |
| — Number of connectable IO Devices for RT, max. | 16 |
| — of which in line, max. | 16 |
| — Activation/deactivation of IO Devices | Yes |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8 |
| — Updating time | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |
| PROFINET IO Device | |
| Services | |
| — PG/OP communication | Yes |
| — S7 routing | Yes |

| | |
|---|-----|
| — Isochronous mode | No |
| — Open IE communication | Yes |
| — IRT | No |
| — MRP | No |
| — MRPD | No |
| — PROFINergy | Yes |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 2 |

Protocols

| | |
|-----------------------------------|-------------------------|
| Supports protocol for PROFINET IO | Yes |
| PROFIBUS | Yes; CM 1243-5 required |
| AS-Interface | Yes; CM 1243-2 required |

Protocols (Ethernet)

| | |
|----------|-----|
| • TCP/IP | Yes |
| • DHCP | No |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |

Open IE communication

| | |
|------------------------|------------|
| • TCP/IP | Yes |
| — Data length, max. | 8 kbyte |
| • ISO-on-TCP (RFC1006) | Yes |
| — Data length, max. | 8 kbyte |
| • UDP | Yes |
| — Data length, max. | 1 472 byte |

Web server

| | |
|-------------------------|-----|
| • User-defined websites | Yes |
|-------------------------|-----|

Further protocols

| | |
|----------|-----|
| • MODBUS | Yes |
|----------|-----|

Communication functions

S7 communication

| | |
|---------------------------|--|
| • supported | Yes |
| • as server | Yes |
| • as client | Yes |
| • User data per job, max. | See online help (S7 communication, user data size) |

Web server

| | |
|-------------|-----|
| • supported | Yes |
|-------------|-----|

Number of connections

| | |
|-----------|-----------------|
| • overall | 16; dynamically |
|-----------|-----------------|

Test commissioning functions

| Status/control | |
|---|--|
| • Status/control variable | Yes |
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing | |
| • Forcing | Yes |
| Diagnostic buffer | |
| • present | Yes |
| Traces | |
| • Number of configurable Traces | 2 |
| • Memory size per trace, max. | 512 kbyte |
| Integrated Functions | |
| Number of counters | 6 |
| Counting frequency (counter) max. | 100 kHz |
| Frequency measurement | Yes |
| controlled positioning | Yes |
| Number of position-controlled positioning axes, max. | 8 |
| Number of positioning axes via pulse-direction interface | Up to 4 with SB 1222 |
| PID controller | Yes |
| Number of alarm inputs | 4 |
| Potential separation | |
| Potential separation digital inputs | |
| • Potential separation digital inputs | Functional isolation (Optocoupler) |
| EMC | |
| Interference immunity against discharge of static electricity | |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes |
| — Test voltage at air discharge | 8 kV |
| — Test voltage at contact discharge | 6 kV |
| Interference immunity to cable-borne interference | |
| • Interference immunity on supply lines acc. to IEC 61000-4-4 | Yes |
| • Interference immunity on signal cables acc. to IEC 61000-4-4 | Yes |
| Interference immunity against voltage surge | |
| • on the supply lines acc. to IEC 61000-4-5 | Yes |
| Interference immunity against conducted variable disturbance induced by high-frequency fields | |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class A, for use in industrial areas | Yes; Group 1 |

- Limit class B, for use in residential areas

Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011

Degree and class of protection

Degree of protection acc. to EN 60529

- IP20

Yes

Standards, approvals, certificates

CE mark

Yes

UL approval

Yes

cULus

Yes

FM approval

Yes

RCM (formerly C-TICK)

Yes

KC approval

Yes

Marine approval

Yes

Highest safety class achievable in safety mode

- Performance level according to ISO 13849-1
- SIL acc. to IEC 61508

PLe

SIL 3

Ambient conditions

Free fall

- Fall height, max.

0.3 m; five times, in product package

Ambient temperature during operation

- min.
- max.
- horizontal installation, min.
- horizontal installation, max.
- vertical installation, min.
- vertical installation, max.

0 °C

55 °C

0 °C

55 °C

0 °C

45 °C

Ambient temperature during storage/transportation

- min.
- max.

-40 °C

70 °C

Air pressure acc. to IEC 60068-2-13

- Storage/transport, min.
- Storage/transport, max.

660 hPa

1 139 hPa

Relative humidity

- Operation, max.

95 %; no condensation

Vibrations

- Vibration resistance during operation acc. to IEC 60068-2-6
- Operation, tested according to IEC 60068-2-6

2 g (m/s²) wall mounting, 1 g (m/s²) DIN rail

Yes

Shock testing

- tested according to IEC 60068-2-27

Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms

Pollutant concentrations

• SO2 at RH < 60% without condensation

S02: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free

Configuration

Programming

Programming language

| | |
|-------|---------------------|
| — LAD | Yes; incl. failsafe |
| — FBD | Yes; incl. failsafe |
| — SCL | Yes |

Know-how protection

| | |
|---|-----|
| • User program protection/password protection | Yes |
| • Copy protection | Yes |
| • Block protection | Yes |

Cycle time monitoring

| | |
|--------------|-----|
| • adjustable | Yes |
|--------------|-----|

Dimensions

| | |
|--------|--------|
| Width | 110 mm |
| Height | 100 mm |
| Depth | 75 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 435 g |
|-----------------|-------|

last modified: 11/28/2017