

# ADAM-4541 ADAM-4542+ ADAM-4561/4562

**Multi-mode Fiber Optic to RS-232/422/485 Converter**  
**Single-mode Fiber Optic to RS-232/422/485 Converter**  
**1-port Isolated USB to RS-232/422/485 Converter**



ADAM-4541



ADAM-4542+



ADAM-4561/4562



## Specifications

### General

- Power Input Unregulated 10 ~ 30 V<sub>DC</sub>
- Connectors 1 x plug-in terminal block (#14 ~ 22 AWG)  
2 x ST fiber connector
- Power Consumption 1.5 W @ 24 V<sub>DC</sub>

### Serial Communications

- Communication Mode Asynchronous
- Speed Modes (bps) 1,200, 2,400, 4,800, 9,600, 19.2 k, 38.4 k, 57.6 k, 115.2 k and RS-232/422 mode (switchable)
- Transmission Mode Full/half duplex, bidirectional

### Fiber Optic Communications

- Optical Power Budget (Attenuation) 12.5 dB (measured with 62.5/125 μm)
- Transmission Distance 2.5 km
- Transmission Mode Multi mode (Send and Receive)
- Wavelength 820 nm

## Specifications

### General

- Power Input Unregulated 12 ~ 24 V<sub>DC</sub>
- Connectors 1 x plug-in terminal block (#14 ~ 22 AWG)  
(RS-232/422/485)  
1 x SC fiber connector
- Power Consumption 3 W @ 24 V<sub>DC</sub>
- Operation Modes Support Point-to-Point, Redundant\* and Ring (half-duplex)
- Redundant Transfer Time 1 μs

### Serial Communications

- Communication Mode Asynchronous
- Speed Modes (bps)\* 1,200, 2,400, 4,800, 9,600, 19.2 k, 38.4 k, 57.6 k, 115.2 k, 230.4 k, 460.8 k, 921.6 k and RS-232/422/485 mode (switchable)
- Transmission Modes Full/half duplex, bidirectional

### Fiber Optic Communications

- Optical Power Budget (Attenuation) 15 dB
- Transmission Distance 15 km
- Transmission Mode Single mode (Send and Receive)
- Wavelength 1310 nm

## Specifications

### General

- Connectors Network: USB-type A connector (type A to type B cable provided)  
Serial:  
ADAM-4561 1 x plug-in terminal (#14 ~ 22 AWG) (3-wire RS-232/422/485)  
ADAM-4562 1 x DB-9 serial connectors (9-wire RS-232)

### Isolation Voltage

- ADAM-4561: 3,000 V<sub>DC</sub>
- ADAM-4562: 2,500 V<sub>DC</sub>

### Power Consumption

- ADAM-4561: 1.5 W @ 5 V
- ADAM-4562: 1.1 W @ 5 V

### Driver Support

- ADAM-4561: Windows 2000/XP/Vista/7/8 (32&64-bit)
- ADAM-4562: Windows 2000/XP/Vista/7/8(32&64-bit)

### USB Specification Compliance

- ADAM-4561: USB 2.0
- ADAM-4562: USB 2.0

### Serial Communications

- Speed Modes (bps) 75 bps to 115.2 kbps
- Transmission Modes Full/half duplex, bidirectional

## Common Specifications

### Environment

- Operating Humidity 5 ~ 95% RH
- Operating Temperature ADAM-4541/4542+: -10 ~ 70°C (14 ~ 158°F)  
ADAM-4561/4562: 0 ~ 70°C (32 ~ 158°F)
- Storage Temperature -25 ~ 85°C (-13 ~ 185°F)

## Ordering Information

- ADAM-4541 Multi-mode Fiber to RS-232/422/485 Converter
- ADAM-4542+ Single-mode Fiber to RS-232/422/485 Converter
- ADAM-4561 1-port Isolated USB to RS-232/422/485 Converter
- ADAM-4562 1-port Isolated USB to RS-232 Converter

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Controllers](#) category:*

*Click to view products by [Advantech](#) manufacturer:*

Other Similar products are found below :

[CS1WCN223](#) [CS1WCN713](#) [CS1WKS001E](#) [61F-11NH](#) [61FGPN8DAC120](#) [61F-GP-NT AC110](#) [61F-GPN-V50-AC110](#) [70177-1011](#) [F03-03](#)  
[HAS B](#) [F03-03 HAS C](#) [F03-31](#) [81513201](#) [81513535](#) [81550401](#) [FT1A-C12RA-W](#) [88981106](#) [H2CAC24A](#) [R88A-CAGA005S](#) [R88A-](#)  
[CRGB003CR-E](#) [R88ARR080100S](#) [R88A-TK01K](#) [DCN1-1](#) [DTB4896VRE](#) [DTB9696CVE](#) [DTB9696LVE](#) [MR-50LF+](#) [E53-AZ01](#) [E53E8C](#)  
[E5CWLQ1TCAC100240](#) [B300LKL21](#) [NE1ASCPU02EIPVER11](#) [NE1SCPU01](#) [NE1SDRM21U](#) [NSCXDC1V3](#) [NSH5-232CW-3M](#)  
[NT20SST122BV1](#) [NV3Q-SW41](#) [NV4W-ATT01](#) [NV-CN001](#) [OAS-160-N](#) [K31S6](#) [K33-L1B](#) [K3TX-AD31A](#) [L595020](#) [SRS2-1](#) [G32X-V2K](#)  
[26546803](#) [26546805](#) [26546831](#) [CJ1W-OD204](#)