



<b>BN 82427</b>
<b>Pozi flat countersunk head screws</b>
form Z
Steel case-hardened 400 HV
zinc plated black

**!** Fasteners steel case-hardened  $\geq 320$  HV electroplated coatings: Susceptible to hydrogen embrittlement! Further notice to residual risks can be found in the introduction section (I).

	$\varnothing$ nominal	d <sub>1</sub>	d <sub>2</sub> max.	k max.		m~	t min.	t max.	L
	2,2	2,2	3,8	1,2	1	2,2	0,95	1,2	6
									8
									10
									12
									14
									16
	2,5	2,5	4,7	1,5	1	3	1,45	1,75	6
									8
									10
									12
									14
									16
	3	3	5,5	1,65	1	3,2	1,6	2	8
									10
									12
									14
									16
									20
									25
	3,5	3,5	7,3	2,35	2	4,3	1,75	2,2	8
									10
									12
									14
									16

	<b>ø nominal</b>	<b>d<sub>1</sub></b>	<b>d<sub>2</sub> max.</b>	<b>k max.</b>		<b>m~</b>	<b>t min.</b>	<b>t max.</b>	<b>L</b>
	3,5	3,5	7,3	2,35	2	4,3	1,75	2,2	20
									25
	4	4	8,4	2,7	2	4,6	2,05	2,5	8
									10
									12
									14
									16
									20
									25