



BN 82428
Pozi pan head screws
form Z
Steel case-hardened 400 HV
zinc plated black

! ISO 4042
 Fasteners hardness ≥ 320 HV with electroplated coatings:
 Susceptible to hydrogen embrittlement!
 Further notice to residual risks can be found in the introduction section.

	\varnothing nominal	d ₁	d ₂ max.	k max.		m~	t min.	t max.	L
	2,2	2,2	4	1,6	1	2,3	1	1,3	5
									6
									8
									10
									12
									14
									16
	2,5	2,5	5	2,1	1	2,6	1,1	1,5	6
									8
									10
									12
									14
									16
	3	3	5,6	2,4	1	2,9	1,35	1,75	6
									8
									10
									12
									14
									16
									20
									25
	3,5	3,5	7	2,6	2	3,9	1,45	1,9	8

	∅ nominal	d ₁	d ₂ max.	k max.		m~	t min.	t max.	L
	3,5	3,5	7	2,6	2	3,9	1,45	1,9	10
									12
									14
									16
									20
									25
	4	4	8	3,1	2	4,4	1,9	2,35	8
									10
									12
									14
									16
									20
									25
	5	5	9,5	3,7	2	4,6	2,3	2,75	10
									12
									14
									16
									20
									25